

SIRIUS HRI 230 W

SIRIUS HRI | High-pressure discharge lamps with reflector



Areas of application

- Concert lighting
- Club and disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product family benefits

- Lightweight and compact reflector lamps
- Perfectly suited for small and lightweight moving heads
- Optimized burner design allows any burning position
- High luminance through very short arc and high pressure
- Bright light for brilliant light effects
- Long lifetime
- Easy lamp replacement
- Stable light output over the entire lifetime



April 25, 2024, 01:42:07 SIRIUS HRI 230 W

Technical data

Electrical data

Nominal wattage	23000 W
Nominal current	33 A
Ignition voltage	2.5 kVp
Nominal voltage	700 V


Photometrical data

Nominal luminous flux	9500 lm
Color temperature	8000 K
Color rendering index Ra	75
Maximum color temperature	8000 K

Light technical data

Focal length	34.5 mm
Aperture window, maximum	5x3.8 mm

Dimensions & weight



Diameter	510 mm
Length	545 mm
Arc length	1.0 mm

Lifespan

2500 h

Additional product data

Category CORE

Capabilities

Burning position	Any
Cooling	Forced
Working distance	34.5 mm

Certificates & standards

EEI – Energy Label	A
--------------------	---

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	05-03-2024
Primary Article Identifier	4008321678225 4008321810311
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

	-			
Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
SIRIUS HRI 230 W	Unpacked 1	55 mm x 51 mm x 51 mm	0.14 dm³	60.00 g
SIRIUS HRI 230 W	Shipping carton box 60	595 mm x 400 mm x 186 mm	44.27 dm ³	5500.00 g
SIRIUS HRI 230 W	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm³	108.00 g
SIRIUS HRI 230 W	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm ³	262.00 g
SIRIUS HRI 230 W	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm³	3101.00 g
	SIRIUS HRI 230 W SIRIUS HRI 230 W SIRIUS HRI 230 W SIRIUS HRI 230 W	(Pieces/Unit)SIRIUS HRI 230 WUnpacked 1SIRIUS HRI 230 WShipping carton box 60SIRIUS HRI 230 WFolding carton box 1SIRIUS HRI 230 WShipping carton box 2SIRIUS HRI 230 WShipping carton box 2	(Pieces/Unit)x width x height)SIRIUS HRI 230 WUnpacked 155 mm x 51 mm x 51 mmSIRIUS HRI 230 WShipping carton box 60595 mm x 400 mm x 186 mmSIRIUS HRI 230 WFolding carton box 187 mm x 87 mm x 103 mmSIRIUS HRI 230 WFolding carton box 187 mm x 87 mm x 103 mmSIRIUS HRI 230 WShipping carton box 2186 mm x 96 mm x 115 mmSIRIUS HRI 230 WShipping carton box 2186 mm x 96 mm x 115 mm	(Pieces/Unit)x width x height)SIRIUS HRI 230 WUnpacked 155 mm x 51 mm x 51 mm0.14 dm³SIRIUS HRI 230 WShipping carton box 60595 mm x 400 mm x 186 mm44.27 dm³SIRIUS HRI 230 WFolding carton box 187 mm x 87 mm x 103 mm0.78 dm³SIRIUS HRI 230 WFolding carton box 287 mm x 87 mm x 103 mm0.78 dm³SIRIUS HRI 230 WShipping carton box 2186 mm x 96 mm x 115 mm2.05 dm³SIRIUS HRI 230 WShipping carton box 21507 mm x 203 mm x 27.17 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.