

SIRIUS HRI 470 W RO

SIRIUS HRI | High-pressure discharge lamps with reflector



Areas of application

- Concert lighting
- Club and disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product family benefits

- Lightweight and compact reflector lamps
- Perfectly suited for small and lightweight moving heads
- Optimized burner design allows any burning position
- High luminance through very short arc and high pressure
- Bright light for brilliant light effects
- Long lifetime
- Easy lamp replacement
- Stable light output over the entire lifetime



Technical data


Electrical data

Nominal wattage	470.00 W
Nominal current	5.3 A
Nominal voltage	83.0 V

Photometrical data

Nominal luminous flux	19500 lm
Color temperature	7500 K
Color rendering index Ra	80

Dimensions & weight



Diameter	60.0 mm
Length	67.0 mm
Arc length	1.3 mm

Lifespan

Lifespan	1500 h
----------	--------

Additional product data

Category	CUSTOMIZED
----------	------------

Capabilities

Burning position	Any
Working distance	48 mm

Certificates & standards

EEL – Energy Label	A
--------------------	---

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899476998 4052899477018 4062172392556
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899476998	SIRIUS HRI 470 W RO	Unpacked 1	- x - x -		140.00 g
4052899477001	SIRIUS HRI 470 W RO	Shipping carton box 60	414 mm x 334 mm x 343 mm	47.43 dm ³	9904.00 g
4052899477018	SIRIUS HRI 470 W RO	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm ³	188.00 g
4052899477025	SIRIUS HRI 470 W RO	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm ³	422.00 g
4052899477032	SIRIUS HRI 470 W RO	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm ³	4701.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.