

64670 500 W 240 V

Halogen studio lamps, single-ended



Areas of application

- Professional film and TV work
- Theater and concert stages
- Entertainment

Product family features

- Operation at mains voltage: 120 V | 230 V | 240 V
- Color temperature: 3,000 K (with longer lifespan)
- Color temperature: 3,200 K (for professional film and TV work)



Technical data

Product information

Order reference	64670
-----------------	-------

Electrical data

Nominal wattage	500.00 W
Nominal voltage	240 V
On-mode power	520.00 W
Energy consumption in on-mode	520.0 kWh/1000h

Photometrical data

Color rendering index Ra	100
Φ_{use} value refers to luminous flux ..	360
Correlated color temperature CCT	3076 K
Useful luminous flux (Φ_{use})	10510 lm
Chromaticity coordinate x	0.432
Chromaticity coordinate y	0.402

Dimensions & weight



Diameter	23.0 mm
Length	90.0 mm
Light center length (LCL)	46.5 mm
Illuminated field	11.0*11.0 mm ²
Filament diameter	11.0 mm

Lifespan

Lifespan	300 h
----------	-------

Additional product data

Base (standard designation)	GY9.5
Lighting technology used	HL

Capabilities

Burning position	s90
------------------	-----

Certificates & standards

Energy efficiency class	G
-------------------------	---

Country specific categorizations

ANSI code	GCV/GVH
LIF	T/25
Order reference	64670

Logistical data

EAN 10 of contained light source	4008321624031
----------------------------------	---------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	22-04-2024
Primary Article Identifier	4050300283449 4008321624031
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321624031	64670 500 W 240 V	Folding carton box 1	40 mm x 40 mm x 129 mm	0.21 dm ³	59.00 g
4008321624048	64670 500 W 240 V	Shipping carton box 12	178 mm x 137 mm x 152 mm	3.71 dm ³	912.00 g
4050300283449	64670 500 W 240 V	Folding carton box 1	143 mm x 46 mm x 46 mm	0.30 dm ³	50.33 g
4050300283456	64670 500 W 240 V	Shipping carton box 25	245 mm x 165 mm x 245 mm	9.90 dm ³	1370.67 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

A summary of studio lamps can be found on the halogen studio lamps poster.
For more information on halogen lamps for studio, stage and TV see the brochure:
"Good news for show business"
"Halogen High Voltage Lamps" cross reference list

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.