

# XBO 150 W/1 OFR

XBO Xenon short-arc lamps without reflector | Xenon short-arc lamps without reflector

### Product family benefits

- Very high luminance (point light source)
- Continual color quality, irrespective of lamp type and lamp wattage
- Constant light color throughout the life of the lamp
- Long lamp life

#### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- High color rendering index: R<sub>a</sub> >
- Continuous spectrum in the visible range
- High arc stability
- Hot restart capability
- Dimmable
- Instant light on starting



April 25, 2024, 01:42:07 XBO 150 W/1 OFR

## Product datasheet

### Technical data

### **Electrical data**


Lamp wattage	130 W
Lamp current	75 A
Type of current	DC

### Photometrical data

Nominal luminous flux	3000 lm
Luminous intensity	300 cd <sup>1)</sup>
Luminance	15000 cd/cm <sup>2 1)</sup>

1) Typical initial photometric value

### **Dimensions & weight**



Length	1500 mm
Length with base excl. base pins/connection	127.00 mm
Product weight	7500 g

### Lifespan

Lifespan	1200 h
Enespan	1200 11

### Additional product data

Base anode (standard designation)	SFc12-4
Base cathode (standard designation)	SFcX12-4

### Capabilities

Cooling	Forced
Burning position	s15 <sup>1)</sup>
Application	Other

### Product datasheet

<sup>1)</sup> Anode (+) on top

### **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	05-03-2024		

Primary Article Identifier	4050300508368
Declaration No. in SCIP database	In work


### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300508368	OSRXBO15010FR	-	-	-
4050300508368	OSRXBO15010FR	-	-	-

### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, XBO lamps must only be operated in appropriate enclosed casings. Always use the protective jackets supplied when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.



#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300508368	XBO 150 W/1 OFR	Folding carton box 1	100 mm x 59 mm x 245 mm	1.45 dm³	166.00 g
4050300508375	XBO 150 W/1 OFR	Shipping carton box 10	256 mm x 312 mm x 213 mm	17.01 dm³	1874.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

Further technical information on XBO lamps and information for manufacturers of operating equipment can be requested directly from OSRAM.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.