

XBO 1600 W/HS XL OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W



Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: R_a >








Product datasheet

Technical data

Electrical data

Nominal current	65 A
Current control range	5075 A
Nominal wattage	160000 W
Nominal voltage	230 V

Dimensions & weight



Diameter	460 mm
Length	2350 mm
Length with base excl. base pins/connection	205.00 mm
Light center length (LCL)	95.0 mm ¹⁾
Cable/wire length, input side	-
Electrode gap cold	3.8 mm
Product weight	30100 g

 $^{^{1)}}$ Distance from end of base to tip of electrode (cold)

Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C

Lifespan

Lifespan	2500 h

Additional product data

Base anode (standard designation)	SFa27-11
Base cathode (standard designation)	SFcX27-8

Capabilities

Product datasheet

Cooling	Forced
Burning position	s20/p20 ¹⁾

 $^{^{1)}}$ For vertical burning position: anode (+) on top

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	19-05-2023	
Primary Article Identifier	4008321299925	
Candidate List Substance 1	Lead	
CAS No. of substance 1	7439-92-1	
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.	
Declaration No. in SCIP database	4ED7A678-5BF0-416C-B869-898F17F9AE02	

Product datasheet

-
ļ

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.