

# XBO 4500 W/HS XL OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W



#### Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

## Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

#### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: R<sub>a</sub> >








## Product datasheet

#### Technical data

### **Electrical data**

Nominal current	135 A
Current control range	80150 A
Nominal wattage	450000 W
Nominal voltage	320 V

### **Dimensions & weight**



Diameter	700 mm
Length	4130 mm
Length with base excl. base pins/connection	370.00 mm
Light center length (LCL)	171.0 mm <sup>1)</sup>
Cable/wire length, input side	400 mm
Electrode gap cold	7.5 mm
Product weight	102300 g
Cable length	4000

 $<sup>^{</sup>m 1)}$  Distance from end of base to tip of electrode (cold)

### Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C
--	--------

### Lifespan

Lifespan	1400 h

## Additional product data

Base anode (standard designation)	SFaX30-9.5
Base cathode (standard designation)	SFa30-7.9

## Product datasheet

## Capabilities

Cooling	Forced <sup>1)</sup>
Burning position	s15/p15 <sup>2)</sup>

 $<sup>^{1)}</sup>$  Vertical and horizontal

### **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration	05-03-2024			
Primary Article Identifier	4008321412881			
Candidate List Substance 1	Lead			
CAS No. of substance 1	7439-92-1			
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.			
Declaration No. in SCIP database	2a7bfa41-544e-40aa-a314-c9fc5872b500			

<sup>2)</sup> For vertical burning position: anode (+) on top

### Product datasheet

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321412881	XBO 4500 W/HS XL OFR	Shipping carton box	590 mm x 234 mm x 229 mm	31.62 dm³	2023.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.