OSRAM

SUPER H1

Up to 30% more light





Up to 30% more lightFor better visibility and shorter reaction

For better visibility and shorter reaction times compared to standard halogen lamps



Enhanced illumination

For extra confidence



Convincing price-performance ratio

For better visibility at a reasonable price



Up to 30% more light on the road

SUPER headlight lamps offer more performance for the most important lamp types. With up to 30% more light compared to standard lamps, signs, obstacles and hazards are more rapidly recognized.

Technical data

Product information

Order reference	64150SUP	
Application (Category and Product specific)	Halogen headlight lamp	

Electrical data


Power input	68 W ¹⁾
Nominal voltage	12.0 V
Nominal wattage	55.00 W
Test voltage	13.2 V

¹⁾ Maximum

Photometrical data

Luminous flux	1550 lm	
Luminous flux tolerance	±15 %	
Color temperature	3200 K	

Dimensions & weight



Diameter	12.0 mm
Product weight	6.30 g
Length	67.5 mm

Lifespan

Lifespan B3	150 h
Lifespan Tc	350 h

Additional product data

|--|

Capabilities

Certificates & standards

ECE category	H1
--------------	----

Country specific categorizations

Order reference	64150SUP

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration 05-03-2024				
Primary Article Identifier	4050300479408 4050300484648 4062172257107 4062172346542			
Candidate List Substance 1	No declarable substances contained			
Declaration No. in SCIP database	In work			

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300479408	OSRA64150SUP	-	-	-
4050300479415	OSRA64150SUP	-	-	-
4050300479408	OSRA64150SUP	-	-	-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300479408	SUPER H1	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm ³	9.00 g
4050300479415	SUPER H1	Bundle 10	113 mm x 50 mm x 70 mm	0.40 dm ³	91.00 g
4050300479422	SUPER H1	Shipping carton box 100	122 mm x 109 mm x 361 mm	4.80 dm ³	1005.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



















Product datasheet | SUPER © 2024, OSRAM GmbH. All rights reserved.