Product datasheet

DIADEM CHROME PY21W

Only amber during operation



Chrome design
Thanks to cutting edge interference and absorber coating

Amber when ON
Only amber when operating, otherwise almost invisible

Homogenous appearance
Reflector has a fully homogenous chrome look



The design light with chrome look

OSRAM DIADEM CHROME signal lamps have a strikingly exclusive design: their chrome look made possible by a cutting edge interference and absorber coating. The lamps emit amber light only when operational. At other times, they are almost invisible and have no irritating color effects. DIADEM CHROME lamps are ideal for all indicator lights with clear covers.

© 2024, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

Product information

Order reference	7507DC
Application (Category and Product specific)	Auxiliary lamp


Electrical data

Power input	25 W
Nominal voltage	12.0 V
Nominal wattage	21.00 W
Power input tolerance	±6 %
Test voltage	13.5 V

Photometrical data

Luminous flux	280 lm
Luminous flux tolerance	±20 %

Dimensions & weight



Length	52.6 mm
Diameter	25.0 mm
Product weight	8.00 g

Lifespan

Lifespan B3	100 h
Lifespan Tc	250 h

Additional product data

Base (standard designation)	BAU15s

© 2024, OSRAM GmbH. All rights reserved.

Capabilities

Technology	AUX

Certificates & standards

ECE category	PY21W

Country specific categorizations

Order reference	7507DC

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	05-03-2024
Primary Article Identifier	4008321972774 | 4052899241657 | 4052899417977 | 4052899418011 | 4062172211529 | 4062172271950 | 4052899979918 | 4062172394857
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321972774	DIADEM CHROME PY21W	Blister 2	- x - x -		
4008321972781	DIADEM CHROME PY21W	Shipping carton box 20	279 mm x 115 mm x 146 mm	4.68 dm^3	360.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM

© 2024, OSRAM GmbH. All rights reserved.