

## OT 60/220...240/12 P

CV Power supplies 12 V



### Product family benefits

- Versatile scope of application due to output power range of up to 120 W
- Very high efficiency
- IP rating: up to IP67
- High surge protection: up to 3 kV (L-N) / 6 kV (L/N-PE)

### Areas of application

- Suitable for indoor and outdoor installations
- Ideal for mounting in very tight spaces

Technical data

Electrical data

Nominal input voltage	220...240 V
Mains frequency	50...60 Hz
Input voltage AC	198...264 V <sup>1)</sup>
Total harmonic distortion	< 20 %
Power factor $\lambda$	098/093 <sup>2)</sup>
Device power loss	9.0 W
Inrush current	35 A <sup>3)</sup>
Max. ECG no. on circuit breaker 10 A (B)	11
Max. ECG no. on circuit breaker 16 A (B)	17
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L-N)	3 kV
Nominal output voltage	12.5 V <sup>4)</sup>
U-OUT (working voltage)	12.5 V
Nominal output power	60 W <sup>5)</sup>
Galvanic isolation	SELV
Galvanic isolation primary/secondary	3.75 kV <sup>6)</sup>

<sup>1)</sup>  $V_{AC}$  / Permitted voltage range  
<sup>2)</sup> Full load at 230 V/Half load at 230 V  
<sup>3)</sup>  $t_{width} = 170 \mu s$  (measured at 50 %  $I_{peak}$ )  
<sup>4)</sup>  $\pm 0.5 V$   
<sup>5)</sup> Partial load 0...60 W  
<sup>6)</sup> SELV-equivalent

Dimensions & weight



Mounting hole spacing, length	171.0 mm
Product weight	70000 g
Cable cross-section, input side	1.0 mm <sup>2</sup> <sup>1)</sup>

Product datasheet

Cable cross-section, output side	1.0 mm <sup>2</sup> <sup>1)</sup>
Wire preparation length, input side	10 mm
Wire preparation length, output side	10 mm
Cable/wire length, input side	500 mm
Cable/wire length, output side	500 mm
Mounting hole spacing, width	14.0 mm <sup>2)</sup>
Length	1800 mm
Width	500 mm
Height	340 mm

<sup>1)</sup> Flexible

<sup>2)</sup> Side mounting

Colors & materials

Casing material	Metal
-----------------	-------

Temperatures & operating conditions

Ambient temperature range	-25...+55 °C
Maximum temperature at tc test point	80 °C
Max.housing temperature in case of fault	100 °C
Temperature range at storage	-40...+85 °C
Permitted rel. humidity during operation	5...85 % <sup>1)</sup>

<sup>1)</sup> Non-condensing

Lifespan

ECG lifetime	50000 h <sup>1)</sup>
--------------	-----------------------

<sup>1)</sup> At T<sub>case</sub> = 70°C at T<sub>c</sub> point / 10% failure rate

Additional product data

Successor EAN	4062172133487
---------------	---------------

Capabilities

Dimmable	No
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
No-load proof	Yes
Suitable for fixtures with prot. class	II
Number of channels	1

Certificates & standards

--	--

Product datasheet

Approval marks – approval	CE / ENEC 18 / CB / CCC / RCM / EAC / BIS
Standards	Acc. to IEC 61347-1/Acc. to IEC 61347-2-13/Acc. to IEC 62384/Acc. to CISPR 15/Acc. to IEC 61000-3-2/Acc. to IEC 61000-3-3/Acc. to IEC 61547
Protection class	II
Type of protection	IP67




Logistical data

Commodity code	850440829000
----------------	--------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	14-04-2022
Primary Article Identifier	4008321790811
Declaration No. in SCIP database	In work

Download Data

File	
	Product Datasheet 340365_OPTOTRONIC OT 60220-24012 P
	Brochures OPTOTRONIC constant-voltage LED power supplies and controls (EN)
	Declarations of conformity 728507_EU Declaration OT

Ecodesign regulation information:

Intended for use with LED modules.  
The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321790811	OT 60/220...240/12 P	Shipping carton box 10	574 mm x 323 mm x 137 mm	25.40 dm <sup>3</sup>	8650.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.