

PrevaLED SKY

with IP connector



Product family features

- Type of protection: IP66
- Impact resistance: IK08
- Version with 6,500 K color temperature available as make-to-order

Product family benefits

- Easy installation of connector, no manual wiring required
- Integrated IP67 connector for easier handling
- Optimized light distribution on the road due to specially designed optics
- Integrated heat sink for excellent thermal management
- High energy efficiency with constant current driver
- Allows multiple module configurations in luminaires
- Easy installation and replacement during maintenance
- Long lifetime and good lumen maintenance factor
- 5 year guarantee

Areas of application

- Road lighting classification ME1 and ME2 according to CIE 115:2010
- Area lighting for high and low ceilings in industrial and commercial buildings
- Floodlight for billboards, sports facilities, advertising
- Outdoor use (only roofed areas)

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Additional product information

- The module should be positioned so that prolonged staring into the module at a distance closer than 2.26 m is not expected.

Sales and Technical Support

Sales and Technical Support www.osram.com

References / Links

For Guarantee see <https://>

- ▶ www.inventronics-light.com/multilevel-guarantees

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.