

HPL (> 130 V)



Areas of application


- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

Product features and benefits


- Ultra compact filament design (UCF) for high lumen output
- Special heat sink base for maximum durability in high temperature applications
- Reinforced pinch seal for extra mechanical strength
- Foam packaging for easier handling and installation
- Optimum system performance with TP22H socket
- Optimum system performance with TP22H socket



Product family datasheet



HPL 575W



HPL 750W

Product family datasheet

Technical data

	Electrical Data		Physical Attributes & Dimensions	Lifetime Data
Product description	Nominal wattage	Nominal voltage	Lamp base	Nominal lifetime
HPL 93728 575 W 230 V	575 W	230 V	G9.5 w/Hsink	400 hr
HPL 93728 LL 575 W 230 V	575 W	230 V	G9.5 w/Hsink	1500 hr
HPL 93728 575 W 240 V	575 W	240 V	G9.5 w/Hsink	400 hr
HPL 93728 LL 575 W 240 V	575 W	240 V	G9.5 w/Hsink	1500 hr
HPL 93729 750 W 230 V	750 W	230 V	G9.5 w/Hsink	300 hr
HPL 93729 LL 750 W 230 V	750 W	230 V	G9.5 w/Hsink	1500 hr
HPL 93729 750 W 240 V	750 W	240 V	G9.5 w/Hsink	300 hr
HPL 93729 LL 750 W 240 V	750 W	240 V	G9.5 w/Hsink	1500 hr

Product family datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.