

## HBO Microlithography Lamps for Canon FPD Systems

### Areas of application


- Microlithography




### Product features and benefits

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Designed for long lasting performance
- Qualified with Canon
- Qualified with Canon





HBO 5000W/CH



HBO MERCURY VAPOUR SHORT ARC LAMPS

Product family datasheet

Technical data

Product description	Electrical Data		Photometric Data	Physical Attributes & Dimensions
	Nominal wattage	Nominal voltage	Light center length (LCL)	Length
HBO 5000 W/CH	5000 W	64 V	156.0 mm <sup>1)</sup>	362.0 mm
HBO 8000 W/CHL	8000 W	81 V	179.0 mm <sup>1)</sup>	434.0 mm
HBO 12000 W/CHL	12000 W	113 V	200.0 mm <sup>1)</sup>	500.0 mm

<sup>1)</sup> Distance from end of base to tip of anode or cathode (cold)

## Product family datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.