

XENARC ULTRA LIFE D2S

Superior life and 10 year guarantee



10 year OSRAM guarantee

For a worry-free driving pleasure.
Register online: www.osram.com/am-guarantee



Extra lifetime

Up to four times longer lifetime
compared to standard xenon lamps



More durability

For longer replacement cycles and
additional reliability and comfort



The durable light with up to four times longer lifetime

XENARC ULTRA LIFE xenon lamps were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers with online registration (www.osram.com/am-guarantee). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

Product datasheet

Technical data


Electrical data

| | |
|-----------------------|---------|
| Power input | 35 W |
| Nominal voltage | 85.0 V |
| Nominal wattage | 35.00 W |
| Test voltage | 13.5 V |
| Power input tolerance | ±3 % |

Photometrical data

| | |
|-------------------------|---------|
| Luminous flux | 3200 lm |
| Luminous flux tolerance | ±15 % |
| Color temperature | 4300 K |

Dimensions & weight



| | |
|----------------|---------|
| Diameter | 9 mm |
| Product weight | 16.00 g |
| Length | 77.0 mm |

Lifespan

| | |
|-----------|----------|
| Guarantee | 10 years |
|-----------|----------|

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | P32d-2 |
|-----------------------------|--------|

Capabilities


| | |
|------------|-----|
| Technology | HID |
|------------|-----|

Certificates & standards

Product datasheet

| | |
|----------------------------------|-------------------|
| ECE category | D2S ¹⁾ |
| Approval marks – approval | E1 approval |

¹⁾ To be operated only with approved electronic control gear





Others graphics

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899425576 | XENARC ULTRA LIFE D2S | Folding carton box 1 | 53 mm x 46 mm x 93 mm | 0.23 dm ³ | 36.00 g |
| 4052899425583 | XENARC ULTRA LIFE D2S | Shipping carton box 4 | 118 mm x 98 mm x 97 mm | 1.12 dm ³ | 175.84 g |
| 4052899425590 | XENARC ULTRA LIFE D2S | Shipping carton box 48 | 371 mm x 256 mm x 232 mm | 22.03 dm ³ | 2361.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File | |
|---|--|
|  | Brochures 724901_ULTRA LIFE Leaflet EN |
|  | 360 Degree Image XENARC ULTRA LIFE D2S 66240ULT |

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Product datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM