

# XENARC ULTRA LIFE D2S

Superior life and 10 year guarantee



**10 year OSRAM guarantee**

For a worry-free driving pleasure. Refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions



**Extra lifetime**

Up to four times longer lifetime compared to standard xenon lamps



**More durability**

For longer replacement cycles and additional reliability and comfort



**The durable light with up to four times longer lifetime**

XENARC ULTRA LIFE xenon lamps for motorcycles were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers ([www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

# Product datasheet

## Technical data


### Electrical Data

Power input	35 W
Nominal voltage	85 V
Nominal wattage	35 W
Power input tolerance	±3 %
Test voltage	13.5 V

### Photometric Data

Nominal luminous flux	3200 lm
Color temperature	4300 K
Luminous flux tolerance	±15 %

### Physical Attributes & Dimensions



Lamp base	P32d-2
Length	77.3 mm
Diameter	9 mm
Diameter	9 mm
Product weight	16.10 g

### Lifetime Data

Guarantee	10 years
-----------	----------

### Capabilities

Technology	HID
------------	-----

### Certificates & standards

ECE category	D2S <sup>1)</sup>
--------------	-------------------


## Product datasheet

Approval marks – approval	E1 approval
---------------------------	-------------

1) To be operated only with approved electronic control gear

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4062172404242   4052899425576   4052899429659
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	ac5968cd-c357-48e1-9a75-7023de759a2e   0e906b5d-b5f0-4059-88bb-8de1f85d5ed2



ref\_pim\_ams\_p\_productinfographic  
s




### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899425576	XENARC ULTRA LIFE D2S	Folding carton box 1	53 mm x 46 mm x 92 mm	0.61 dm <sup>3</sup>	36.00 g
4052899425583	XENARC ULTRA LIFE D2S	Shipping carton box 4	115 mm x 101 mm x 103 mm	1.20 dm <sup>3</sup>	176.00 g
4052899429659	XENARC ULTRA LIFE D2S	Hard Cover Box 2	113 mm x 48 mm x 106 mm	0.61 dm <sup>3</sup>	124.00 g
4062172022064	XENARC ULTRA LIFE D2S	Shipping carton box 4	122 mm x 106 mm x 121 mm	1.56 dm <sup>3</sup>	328.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

### Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures ULTRA LIFE Leaflet EN
	ref_pim_amsproduct360degreeimages XENARC ULTRA LIFE D2S 66240ULT

#### Safety advice

XENARC lamp change is recommended to be carried out by a professional.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM