

# XENARC ULTRA LIFE

Superior life and 10 year guarantee



## 10 year OSRAM guarantee

For a worry-free driving pleasure. Refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions

## Extra lifetime

Up to four times longer lifetime compared to standard xenon lamps

## More durability

For longer replacement cycles and additional reliability and comfort



## The durable light with up to four times longer lifetime

XENARC ULTRA LIFE xenon lamps for motorcycles were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers ([www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

Product family datasheet

Technical data

| Product description                 | Electrical data |                 |                 |                       |              | Photometrical data | Dimensions & weight |
|-------------------------------------|-----------------|-----------------|-----------------|-----------------------|--------------|--------------------|---------------------|
|                                     | Power input     | Nominal voltage | Nominal wattage | Power input tolerance | Test voltage | Luminous flux      | Length              |
| XENARC ULTRA LIFE D1S <sup>1)</sup> | 35 W            | 850 V           | 3500 W          | ±3 %                  | 13.5 V       | 3200 lm            | 832 mm              |
| XENARC ULTRA LIFE D2S <sup>1)</sup> | 35 W            | 850 V           | 3500 W          | ±3 %                  | 13.5 V       | 3200 lm            | 773 mm              |
| XENARC ULTRA LIFE D3S <sup>1)</sup> | 35 W            | 420 V           | 3500 W          | ±3 %                  | 13.5 V       | 3200 lm            | 832 mm              |
| XENARC ULTRA LIFE D4S <sup>1)</sup> | 35 W            | 420 V           | 3500 W          | ±3 %                  | 13.5 V       | 3200 lm            | 773 mm              |

| Product description                 | Diameter | Additional product data     | Capabilities | Certificates & standards | Environmental information<br>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|-------------------------------------|----------|-----------------------------|--------------|--------------------------|----------------------------------------------------------------------------------------------------|
|                                     |          | Base (standard designation) | Technology   | ECE category             | Date of Declaration                                                                                |
| XENARC ULTRA LIFE D1S <sup>1)</sup> | 900 mm   | PK32d-2                     | HID          | D1S <sup>2)</sup>        | 06-03-2024                                                                                         |
| XENARC ULTRA LIFE D2S <sup>1)</sup> | 900 mm   | P32d-2                      | HID          | D2S <sup>2)</sup>        | 06-03-2024                                                                                         |
| XENARC ULTRA LIFE D3S <sup>1)</sup> | 900 mm   | PK32d-5                     | HID          | D3S <sup>2)</sup>        | 06-03-2024                                                                                         |
| XENARC ULTRA LIFE D4S <sup>1)</sup> | 900 mm   | P32d-5                      | HID          | D4S <sup>2)</sup>        | 06-03-2024                                                                                         |

| Product description                 | Primary Article Identifier                                                    | Candidate List Substance 1         | CAS No. of substance 1 | Safe Use Instruction                                                                               |
|-------------------------------------|-------------------------------------------------------------------------------|------------------------------------|------------------------|----------------------------------------------------------------------------------------------------|
| XENARC ULTRA LIFE D1S <sup>1)</sup> | 4052899425514   4052899429598   4052899429635   4052899429611   4062172404211 | Lead                               | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| XENARC ULTRA LIFE D2S <sup>1)</sup> | 4052899425576   4052899429659   4052899429697   4052899429673   4062172404242 | Lead                               | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| XENARC ULTRA LIFE D3S <sup>1)</sup> | 4052899425606   4052899429710   4052899429734   4052899429758   4062172404273 | Lead                               | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| XENARC ULTRA LIFE D4S <sup>1)</sup> | 4052899425637   4052899429772   4052899429819   4052899429796                 | No declarable substances contained |                        |                                                                                                    |

Product family datasheet

| Product description                 | Declaration No. in SCIP database                                            |
|-------------------------------------|-----------------------------------------------------------------------------|
| XENARC ULTRA LIFE D1S <sup>1)</sup> | e59d8923-da88-412b-879a-a321dc37e951   dbae34d6-0162-4aca-9ca3-4b6e003e5fba |
| XENARC ULTRA LIFE D2S <sup>1)</sup> | ac5968cd-c357-48e1-9a75-7023de759a2e   0e906b5d-b5f0-4059-88bb-8de1f85d5ed2 |
| XENARC ULTRA LIFE D3S <sup>1)</sup> | a4977431-0469-4938-bbae-2f7fbc300030   4dac5460-9f2d-4974-8f46-2378b4246f3e |
| XENARC ULTRA LIFE D4S <sup>1)</sup> | In work                                                                     |

<sup>1)</sup> Reduced UV emission/For projection headlights/ECE approval and DOT label  
<sup>2)</sup> To be operated only with approved electronic control gear

Download Data

| File                                                                              |                                                    |
|-----------------------------------------------------------------------------------|----------------------------------------------------|
|  | Brochures<br>724901_ULTRA LIFE Leaflet EN          |
|  | 360 Degree Image<br>XENARC ULTRA LIFE D1S 66140ULT |
|  | 360 Degree Image<br>XENARC ULTRA LIFE D2S 66240ULT |
|  | 360 Degree Image<br>XENARC ULTRA LIFE D3S 66340ULT |
|  | 360 Degree Image<br>XENARC ULTRA LIFE D4S 66440ULT |

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

