

LEDiving BASIC P21W



Product family datasheet

Technical data

Product description	Product information		General Product Information	Electrical Data	
	Application (Category and Product specific)	Product type (off-road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDDriving BASIC \triangleq P21W	Mainly used for signal/ indicator applications	Off-road \triangleq P21W	7356CW	1.44 W	12 V

Product description	Nominal wattage	Test voltage	Photometric Data		Physical Attributes & Dimensions
			Nominal luminous flux	Luminous flux tolerance	Diameter
LEDDriving BASIC \triangleq P21W	1 W	13.5 V	85 lm	± 20 %	20.0 mm

Product description	Diameter	Lifetime Data		Capabilities	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Lifespan B3	Lifespan Tc	Technology	Primary article identifier
LEDDriving BASIC \triangleq P21W	20.0 mm	2000 hr	2000 hr	LED	4052899463318 4052899414471 4052899414457

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDDriving BASIC \triangleq P21W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d093b426-00c5-4f97-9516-27dd98167ef2 ccdfe44b-95fd-4b60-97d3-317a31be77c4 c583693a-46e5-4c4f-83a9-dac2ada6ba15

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

