

LEDDriving BASIC P21W



Product family datasheet

Technical data

Product description	Product information			Electrical data		
	Order reference	Product type (off-road vs. on-road)	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage
LEDDriving BASIC \triangleq P21W	7356CW	Off-road \triangleq P21W	Mainly used for signal/ indicator applications	1.44 W	120 V	120 W

Product description	Test voltage	Photometrical data		Dimensions & weight	Lifespan		Capabilities
		Luminous flux	Luminous flux tolerance	Diameter	Lifespan B3	Lifespan Tc	Technology
LEDDriving BASIC \triangleq P21W	13.5 V	85 lm	± 20 %	2000 mm	2000 h	2000 h	LED

Product description	Environmental information			
	Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1
LEDDriving BASIC \triangleq P21W	06-03-2024	4052899414471 4052899414457 4052899427136 4052899463103 4052899463318	Lead	7439-92-1

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDDriving BASIC \triangleq P21W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	c583693a-46e5-4c4f-83a9-dac2ada6ba15 d093b426-00c5-4f97-9516-27dd98167ef2 1f8b9ac6-80cf-4025-9b20-602066abdedc cef1d027-a386-4f57-ab7c-1d24968ed49e ccdfe44b-95fd-4b60-97d3-317a31be77c4

Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.