OSRAM

LEDriving BASIC T4W



Product family datasheet

Technical data

	Product info	Product information				Electrical data		
Product description	Order reference	Product type (off- road vs. on-road)	Application and Product		Power input	Nominal voltage	Nominal wattage	
LEDriving BASIC ≙ T4W	3750CW	Off-road ≜ Mainly used for T4W signal/ indicator/ interior applications			0.78 W	120 V	065 W	
				Dimension & weight	s Lifespan	1	Capabilities	
Product description	Test voltage		Luminous flux	Diameter	Lifespan B3	Lifespan Tc	Technology	

	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1	
LEDriving BASIC ≙ T4W	06-03-2024	4052899414655 4052899414617 4052899427471 4052899463066 4052899463271	Lead	7439-92-1	

tolerance

950 mm

2000 h

2000 h

LED

±20 %

13.5 V

30 lm

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDriving BASIC	The identification of	dc70588f-5433-
	the Candidate List	4c78-9a81-
	substance is	18450deb8f7c
	sufficient to allow	9add2d47-cd43-
	safe use of the	47d0-90e8-
	article.	b42553d559f6
		a1bf53bb-4f21-4d5b-
		a18e-23d37d00db14
		aadf4566-2f5c-
		420c-940e-
		ab52c14c2128
		4ed996ff-d5b8-4576-
		b168-a975922e67e5

Product family datasheet

Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.