

# LEDiving BASIC T4W



Technical data

Product information

Order reference	3750CW
Product type (off-road vs. on-road)	Off-road ≙ T4W
Application (Category and Product specific)	Mainly used for signal/ indicator/ interior applications


Electrical data

Power input	0.78 W
Nominal voltage	120 V
Nominal wattage	065 W
Test voltage	13.5 V
Power input tolerance	±20 %

Photometrical data

Luminous flux	30 lm
Luminous flux tolerance	±20 %
Color temperature	6000 K
Light color LED	Cool white

Dimensions & weight



Diameter	950 mm
Product weight	148 g
Length	205 mm

Lifespan

Lifespan B3	2000 h
Lifespan Tc	2000 h
Guarantee	4 years

Product datasheet

Additional product data

Base (standard designation)	BA9s
-----------------------------	------

Capabilities

Technology	LED
------------	-----

Country specific categorizations

Order reference	3750CW
-----------------	--------

Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899414655   4052899414617   4052899427471   4052899463066   4052899463271
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	dc70588f-5433-4c78-9a81-18450deb8f7c   9add2d47-cd43-47d0-90e8-b42553d559f6   a1bf53bb-4f21-4d5b-a18e-23d37d00db14   aadf4566-2f5c-420c-940e-ab52c14c2128   4ed996ff-d5b8-4576-b168-a975922e67e5

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899463271	LEDiving BASIC ≙ T4W	Blister 2	- x - x -		
4052899463288	LEDiving BASIC ≙ T4W	Shipping carton box 20	137 mm x 80 mm x 103 mm	1.13 dm³	115.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Brochures LEDiving Retrofits - Exchange overview (EN)

## Product datasheet

### Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.