OSRAM

LEDriving BASIC R10W



Product family datasheet

LEDriving BASIC \triangleq R10W

Technical data

	Product info	Product information			Electrical data		
Product description	Order reference	Product type (off- road vs. on-road)	Application and Product	`	Power input	Nominal voltage	Nominal wattage
LEDriving BASIC ≜ R10W	5108CW	Off-road ≜ Mainly used for R10W signal/ indicator applications Photometrical data Dimensior & weight		ator	1.44 W	120 V	120 W
				Dimensions & weight	Lifespar	1	Capabilities
Product description	Test	Luminous L	uminous	Diameter	Lifespan	Lifespan	Technology

flux

tolerance

±20 %

В3

2000 h

1900 mm

Tc

2000 h

LED

voltage

13.5 V

flux

85 lm

	Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)						
Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1			
LEDriving BASIC ≜ R10W	06-03-2024	4052899414570 4052899414594 4052899427426 4052899463356 4052899463141	Lead	7439-92-1			

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDriving BASIC ≙ R10W	The identification of	2115fbba-97ea-
	the Candidate List	4065-9557-
	substance is	f01077d71065
	sufficient to allow	3d88abbd-dd35-
	safe use of the	4bb0-bea6-
	article.	4442158e669d
		3ad4bf45-0260-
		446d-a214-
		cf1deeca87d9
		b202dc8f-679a-
		4862-8048-
		9e2fbcf9ed99
		1068a570-b34f-
		446b-84ce-
		0f878db5b787

Product family datasheet

Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.