

# LEDDriving BASIC P21W



Technical data

Product information

Order reference	7356CW
Product type (off-road vs. on-road)	Off-road ≙ P21W
Application (Category and Product specific)	Mainly used for signal/ indicator applications

Electrical data

Power input	1.44 W
Nominal voltage	12.0 V
Nominal wattage	1.20 W
Power input tolerance	±20 %
Test voltage	13.5 V

Photometrical data

Color temperature	6000 K
Luminous flux	85 lm
Luminous flux tolerance	±20 %
Light color LED	Cool white

Dimensions & weight

Length	38.2 mm
Diameter	20.0 mm
Product weight	12.02 g

Lifespan

Lifespan B3	2000 h
Lifespan Tc	2000 h
Guarantee	4 years

Product datasheet

Additional product data

Base (standard designation)	BA15s
-----------------------------	-------

Capabilities

Technology	LED
------------	-----

Country specific categorizations

Order reference	7356CW
-----------------	--------

Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899414471   4052899414457   4052899427136   4052899463103   4052899463318
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	c583693a-46e5-4c4f-83a9-dac2ada6ba15   d093b426-00c5-4f97-9516-27dd98167ef2   1f8b9ac6-80cf-4025-9b20-602066abdedc   cef1d027-a386-4f57-ab7c-1d24968ed49e   ccdfe44b-95fd-4b60-97d3-317a31be77c4

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899463318	LEDDriving BASIC ≙ P21W	Blister 2	- x - x -		
4052899463325	LEDDriving BASIC ≙ P21W	Shipping carton box 20	280 mm x 80 mm x 103 mm	2.31 dm³	345.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

## Product datasheet

### Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.