

LEDDriving BASIC P21/5W



Product family datasheet

Technical data

Product description	Product information			Electrical data		
	Order reference	Product type (off-road vs. on-road)	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage
LEDDriving BASIC \triangleq P21/5W	1357CW	Off-road \triangleq P21/5W	Mainly used for signal/ indicator applications	1.44 W	12.0 V	1.20 W

Product description	Power input tolerance	Test voltage	Photometrical data	Dimensions & weight		Lifespan	
			Luminous flux	Length	Diameter	Lifespan B3	Lifespan Tc
LEDDriving BASIC \triangleq P21/5W	± 20 %	13.5 V	85/25 lm	38.2 mm	20.0 mm	2000 h	2000 h

Product description	Additional product data	Capabilities	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Base (standard designation)	Technology	Date of Declaration	Primary Article Identifier
LEDDriving BASIC \triangleq P21/5W	BAY15d	LED	06-03-2024	4052899414518 4052899414495 4052899427327 4052899463295 4052899463080

Product description	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
LEDDriving BASIC \triangleq P21/5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	fe6d71fd-c80e-400d-8cc2-14ed29394294 1d480114-7d33-4144-80cc-0d5f7210d25e e9e1666a-1f1f-4c57-897e-b5d1a43415ca 71710aae-de5e-4bc7-9841-c54466748320 9bf3b981-7442-439c-a86d-e513fc794734

Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.