

PL-SKY-G2 765L150X80T40S W/P

PrevaLED SKY G2 Module | LED modules for street lighting



Product family features

- Available with color temperature: 3,000 K, 4,000 K or 6,500 K
- 5 different optical lenses for diverse application
- Type of protection: IP66 and IK08
- Lifetime: up to 50,000 h (at 450 mA and 700 mA)
- Lifetime: up to 35,000 h (at 960 mA)
- Wide operating temperature range: -30...90 °C
- Certificates: CE, CB, CQC
- Color rendering index R_a: 70

Product family benefits

- High module efficacy: up to 152 lm/W

- Integrated heat sink for optimal thermal management and tailored optical design

Areas of application

- Area illumination for Highbay, Lowbay and Canopy light for industry and outdoor application
- Billboard and floodlight
- Street lighting for ME1 and ME2 road class



Product datasheet

Technical data


Electrical data

Nominal current	0.7 A
Type of current	DC

Photometrical data

Luminous efficacy	132 lm/W
Color rendering index Ra	70

Dimensions & weight



Product weight	350.00 g

Temperatures & operating conditions

Temperature range in operation at Tc point	-3090 °C
Temperature range at storage	-3085 °C

Certificates & standards

Type of protection	ection IP66		
Standards	Acc. to IEC 62471/Acc. to IEC 60598-1/Acc. to EN 60529/Acc. to EN 62031/Acc. to IEC 60598-1 (Class I)/Acc. to EN 55015/Acc. to EN 61547		

Logistical data

Commodity code

854370909900

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration

19-10-2022

Product datasheet

Primary Article Identifier	4052899573994	
Candidate List Substance 1	No declarable substances contained	
Declaration No. in SCIP database	No declarable substances contained	

Download Data

	File
Ę	IES data IES file for PL-SKY-G2 765L150X80T40S

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899573994	PL-SKY-G2 765L150X80T40S W/P	Shipping carton box 12	312 mm x 290 mm x 272 mm	24.61 dm³	4902.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.