Product datasheet

XENARC NIGHT BREAKER LASER D3S

Brightest OSRAM xenon light



Up to 200% more brightness
More light allows to see farther and therefore react sooner compared to the minimum legal standard

Up to 250 m long beam
For better visibility

Up to 20% whiter light
Close to laser look compared to the minimum legal standard



The most powerful xenon light from OSRAM

XENARC NIGHT BREAKER LASER is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 200% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light, close to laser look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER LASER - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.

© 2024, OSRAM GmbH. All rights reserved.

Technical data


Electrical data

Power input	35 W
Nominal voltage	42.0 V
Nominal wattage	35.00 W
Test voltage	13.5 V
Power input tolerance	±3 %

Photometrical data

Luminous flux	3200 lm
Luminous flux tolerance	±15 %
Color temperature	4400 K

Dimensions & weight



Diameter	9 mm
Product weight	60.20 g
Length	83.2 mm

Lifespan

Lifespan B3	2000 h
Lifespan Tc	3000 h

Additional product data

Base (standard designation)	PK32d-5

Capabilities

Technology	HID

© 2024, OSRAM GmbH. All rights reserved.

Certificates & standards

ECE category	D3S [1)]
Approval marks – approval	E1 approval

[1)] To be operated only with approved electronic control gear

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899993150 | 4052899993136 | 4052899993112 | 4052899993099 | 4052899992979
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	83497fdb-f0d9-456b-bd77-0d812a8e2775 | cfe441c2-c423-4f33-a5b0-b2a8b7592c15 | | d751e109-de28-4acf-9d59-e29beb418a68

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899993150	XENARC NIGHT BREAKER LASER D3S	Hard Cover Box 2	- x - x -		89.00 g
4052899993167	XENARC NIGHT BREAKER LASER D3S	Shipping carton box 10	257 mm x 129 mm x 121 mm	4.01 dm^3	1142.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Safety advice

XENARC lamps should be replaced by a qualified mechanic.

This product must only be operated with approved electronic control gear.

Legal advice

Light output compared to the minimum ECE R98/99 requirements

This product must only be operated with approved electronic control gear

XENARC lamps should be replaced by a qualified mechanic

Reduced UV emission | For projection headlights | ECE approval and DOT label

± 450 lm

© 2024, OSRAM GmbH. All rights reserved.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM

© 2024, OSRAM GmbH. All rights reserved.