OSRAM

Lightbar FX500-CB

Higher luminosity guarantees improved safety on the road





Combo Beam Combined beam of light



Lighting distance up to 440 metersImproved far and near field illumination



Beam angle 5°
Exceptionally focused beam angle

Product family datasheet



LED auxiliary lights enhance driving pleasure

Improved far field illumination on dark rural and dirt roads it's no problem for the LEDriving Lightbar FX500-CB. Its 20 intense, high-performance LEDs give the LED high beam a light distance up to 440 meters and ensure improved road safety for drivers. Even at dusk or in compromised lighting conditions, the LED bars for automobiles provide daylight conditions at a strong 6000 Kelvin without needlessly blinding oncoming traffic. The intelligent reflector design diverts the light from the LEDs so that oncoming traffic is only indirectly exposed to the light. The light is evenly distributed at a five degree angle. Robust, durable and versatile Whether used as a LED working light or as an auxiliary high beam for the car the powerful performance and long life of the LEDriving Lightbar FX500-CB make it a compelling choice. Equipped for a wide range of uses, it defies environmental factors and is particularly robust thanks to the quality craftsmanship of its materials and hard-wearing polycarbonate lens. The integrated driver and thermal management system regulates the temperature of the LED automotive headlight and prevents damage caused by overheating. Full polarity protection ensures the LEDs are automatically shut off in the event of excess voltage.Brightness for a wide range of usesThe LEDriving Lightbar FX500-CB is pure pleasure both on and offroad. The ECE-compliant LED auxiliary light ensures better visibility and thus improved safety on roads. In addition, it adds a smart touch that enhances the off-road style of the vehicle. The LED headlight can be mounted on 12V vehicles as well as agricultural machines, utility vehicles, recreational, offroad and 4x4 vehicles. The power package with an intense 5500 lumen brightness scores with the highest optical efficiency and homogeneous light distribution with reduced glare.

Product family datasheet

Technical data

	Product in	Product information		Electrical data			Photomet rical data	
Product description	Order reference	Application and Produc	, , ,	Nominal voltage	Nominal wattage	Test voltage	Luminous flux	
Lightbar FX500-CB	LEDDL104 CB	LEDDL104- Additional high beam 12/24 V 70 W 13.5 V 5500 lm CB application						
	Lifespan	Capabilities	Logistical data Environmental information Information according Art. 33 Regulation (EC) 1907/2006 (F		Art. 33 of EU			
Product description	Lifespan Tc	Technology	Commodit	y code	Date of De	claration	Primary Article Identifier	
Lightbar FX500-CB	5000 h	LED	85122000	900	06-03-202	4	4052899595392	

Product description	Candidate List Substance 1	CAS No. of substance	Safe Use Instruction	Declaration No. in SCIP database
Lightbar FX500-CB	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	3fb4e8db-b861- 4743-a139- 730e69bb83fc

Product family datasheet

Download Data

	File
Z	User instruction LEDriving
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application Working and Driving Lights Amarok Winter
	Movie application LEDriving driving & working lights in application (EN)
D	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
D	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
D	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads

Legal advice

In vehicles with 12/24 volts, auxiliary lights must be installed in pairs

Precise terms and conditions at: www.osram.com/guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaime

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











