

Basic Area G2

Area and Bar Light Engines



Product family features

- Module efficacy: up to 166 lm/W
- Average lifetime (L80 B50): up to 70,000 h (temperature at $T_c = 55\text{ °C}$)
- Available with luminous flux: 2,600 lm
- Available with color temperature: 3,000 K, 4,000 K or 6,500 K
- High initial color consistency: ≤ 3 SDCM
- CE marked, ENEC certified

Product family benefits

- Rectangular shape (540 mm x 270 mm) to fit in multiple square applications
- Easy installation and mounting via interconnection of two modules
- Provides homogenous light suitable for application in area luminaires
- SELV module for easy luminaire design

Areas of application

- Offices
- Hallways, corridors
- Light ceilings

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.