

## VF1000 G4-940-05

VALUE Flex G4 | Linear LED modules for flexible and individualized lighting solutions



### Product family features

- Available in warm white and neutral white
- 3 SDCM, CRI90
- Non-IP and IP66 version available
- 120° viewing angle per module
- Dimmable with PWM technology
- Up to 50,000 hrs lifetime @ tc max

### Product family benefits

- Energy saving low-power flexible LED strip
- Easy installation with track system
- Multi cut-able with CONNECT system

### Areas of application

- Hospitality
- Cabinet lighting
- Signage
- Architecture lighting
- Wall integration



# Product datasheet

## Technical data


### Electrical data

Nominal voltage	24.0 V
Type of current	DC
Rated wattage	50.00 W
Input voltage range	23...25 V
Accidental reverse input voltage protection up to	25 V

### Photometrical data

Light color LED	White
Color rendering index Ra	>90
Luminous efficacy	100 lm/W
Light color (designation)	White

### Dimensions & weight



Length	5000 mm
Product weight	80.00 g
Width	8.00 mm
Height	1.20 mm

### Temperatures & operating conditions

Temperature range at storage	-25...70 °C
------------------------------	-------------

### Certificates & standards

Standards	Acc. to EN62471/EN62778/Acc. to IEC60838/CE/RoHS/Reach
-----------	--

### Logistical data


## Product datasheet

Commodity code	888888888888
----------------	--------------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4062172152839
Declaration No. in SCIP database	In work

### Download Data

File
 IES data IES OF VF 1000 940 G4

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172152839	VF1000 G4-940-05	Shipping carton box 20	465 mm x 275 mm x 208 mm	26.60 dm <sup>3</sup>	2660.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.