OSRAM

LEDriving SL P21W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P21W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

	Electrical Data					Photom etric Data
Product description	Power input	Nominal voltage	Nominal wattage	Power input toleranc e	Test voltage	Nominal luminou s flux
LEDriving SL ≙ P21W	1.8 W	12 V	1 W	±25 %	13.5 V	160 lm

1.0 11 12 1			23 70 13.3 1	100 till		
Physical Attributes	Physical Attributes & Dimensions					
Lamp base	Length	Diamete	er Diam	eter		
BA15s	52.5 mm	25.0 mn	m 25.0	mm		
Lifetime Data	Information		cion according Art. 33 of EU			
Lifespan B3	Lifespan Tc	Primary article identifier	Candidate list substance 1			
1500 hr	4000 hr	4062172348652 4062172152181 4062172401210	Lead			
	Physical Attributes Lamp base BA15s Lifetime Data Lifespan B3	Physical Attributes & Dimensions Lamp base Length BA15s 52.5 mm Lifetime Data Lifespan B3 Lifespan Tc	Lifetime Data Lifetypan B3 Lifespan B3 Lifespan Tc Lifetypan B3 Lifespan Tc Lifetypan B3 Lifespan B3	Physical Attributes & Dimensions Lamp base Length Diameter Diameter BA15s 52.5 mm 25.0 mm 25.0 Lifetime Data Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) Lifespan B3 Lifespan Tc Primary article identifier substance 1 1500 hr 4000 hr 4062172348652 Lead 4062172152181 4062172401210		

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving SL ≜ P21W	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	4b523b49-273b- 43fa-a900- dfef06fdea31 e75f732e-151e- 4392-9807- f15711d460b4 cbc40782-6f5e-4a73- ad3f-4f03b28c1891 431a14a2-e6f5-451f-
			b379-4763b7bc7850

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.