

SharXS HTI




Areas of application

- Concert Lighting
- Club & Disco
- Stage & Theatre
- Studio, TV, & Film
- Architecture & Architainment

Product features and benefits

- SHARXS lamps provide consistent lengths and bases within each SharXS family for simplified fixture designs (Baby SharXS - 93mm, SharXS - 136mm, Maxi SharXS - 220mm)
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Hot restart capability
- Natural tone of light with CRI as high as 90 for "Brilliant" types
- Pre-focus base for accurate lamp installation





SharXS HTI

Product family datasheet

Technical data

Product description	General Product Information			
	Global order reference	Product number (Americas)	Product name (Americas)	Family brand
Baby SharXS HTI 250 W/D5/80	Baby SharXS HTI 250 W/D5/80			
Baby SharXS HTI 300 W/D5/57	Baby SharXS HTI 300 W/D5/57	54298	BABY SHARXS HTI 300W/D5/57 10/CS 1/SKU	Baby SharXS HTI
Baby SharXS HTI 300 W/D5/65	Baby SharXS HTI 300 W/D5/65	54299	BABY SHARXS HTI 300W/D5/65 10/CS 1/SKU	Baby SharXS HTI
Baby SharXS HTI 575 W/D5/56	Baby SharXS HTI 575 W/D5/56	54359	BABY SHARXS HTI 575W/D5/56 10/CS 1/SKU	Baby SharXS HTI
SHARXS HTI 400 W/D3/75 ¹⁾	SHARXS HTI 400 W/D3/75	54241	SHARXS HTI 400W/D3/75 10/CS 1/SKU	SharXS HTI
SHARXS HTI 700 W/D4/60 ²⁾	SHARXS HTI 700 W/D4/60	54282	SHARXS HTI 700W/D4/60 10/CS 1/SKU	SharXS HTI
SHARXS HTI 700 W/D4/75 ³⁾	SHARXS HTI 700 W/D4/75	54242	SHARXS HTI 700W/D4/75 10/CS 1/SKU	SharXS HTI
SHARXS HTI 1200 W/D7/60 ³⁾	SHARXS HTI 1200 W/D7/60	54268	SHARXS HTI 1200W/D7/60 10/CS 1/SKU	SharXS HTI
SharXS 1200W Brilliant ³⁾	SharXS 1200W Brilliant	55188	SHARXS 1200W BRILLIANT 10/CS 1/SKU	
SHARXS HTI 1200 W/D7/75 ²⁾	SHARXS HTI 1200 W/D7/75	54269	SHARXS HTI 1200W/D7/75 10/CS 1/SKU	SharXS HTI
SHARXS HTI 1500 W/D7/60 ⁴⁾	SHARXS HTI 1500 W/D7/60	54319	SHARXS HTI 1500W/D7/60 10/CS 1/SKU	SharXS HTI
Maxi SharXS HTI 1800 W	Maxi SharXS HTI 1800 W	4062172399807	MAXI-SHARXS HTI 1800W 10/CS 1/SKU	
Maxi SharXS HTI 2000 W	Maxi SharXS HTI 2000 W	54328	MAXI SHARXS HTI 2000W/D10/60 10/CS 1/SKU	SharXS HTI

Product description	Lamp type	Electrical Data		
		Nominal wattage	Nominal voltage	Ignition voltage
Baby SharXS HTI 250 W/D5/80		250 W	95 V	2.0 / 20 kVp ⁵⁾
Baby SharXS HTI 300 W/D5/57	DOUBLE ENDED	300 W	75 V	4.5 / 20 kVp
Baby SharXS HTI 300 W/D5/65	DOUBLE ENDED	300 W	95 V	4.5 / 20 kVp
Baby SharXS HTI 575 W/D5/56		575 W	93 V	4.5 / 20 kVp
SHARXS HTI 400 W/D3/75 ¹⁾		400 W	50 V	3.0 / 25 kVp ⁵⁾
SHARXS HTI 700 W/D4/60 ²⁾		700 W	70 V	3.0 / 25 kVp ⁵⁾
SHARXS HTI 700 W/D4/75 ³⁾		700 W	70 V	3.0 / 25 kVp ⁵⁾

Product family datasheet

Product description	Lamp type	Electrical Data		
		Nominal wattage	Nominal voltage	Ignition voltage
SHARXS HTI 1200 W/D7/60 ³⁾		1200 W	96.6 V	5.0 / 35 kVp
SharXS 1200W Brilliant ³⁾		1200 W	90 V	5.0 / 35 kVp
SHARXS HTI 1200 W/D7/75 ²⁾		1200 W	95.3 V	5.0 / 35 kVp
SHARXS HTI 1500 W/D7/60 ⁴⁾		1500 W	110 V	5.0 / 35 kVp
Maxi SharXS HTI 1800 W		1800 W	101 V	
Maxi SharXS HTI 2000 W		2000 W	105 V	

Product description	Nominal current	Type of current	Photometric Data	
			Nominal luminous flux	Color temperature
Baby SharXS HTI 250 W/D5/80	3.3 A	AC	19000 lm	8000 K
Baby SharXS HTI 300 W/D5/57	4.3 A	AC	20000 lm	5700 K
Baby SharXS HTI 300 W/D5/65	3.6 A	AC	22000 lm	6500 K
Baby SharXS HTI 575 W/D5/56	7.2 A	AC	43000 lm	5600 K
SHARXS HTI 400 W/D3/75 ¹⁾	8.5 A	AC	26000 lm	7500 K
SHARXS HTI 700 W/D4/60 ²⁾	11 A	AC	59000 lm	6000 K
SHARXS HTI 700 W/D4/75 ³⁾	10 A	AC	59000 lm	7500 K
SHARXS HTI 1200 W/D7/60 ³⁾	12.4 A	AC	110000 lm	6900 K
SharXS 1200W Brilliant ³⁾	13.3 A	AC	110000 lm	6100 K
SHARXS HTI 1200 W/D7/75 ²⁾	12.6 A	AC	91000 lm	8800 K
SHARXS HTI 1500 W/D7/60 ⁴⁾	13.6 A		145000 lm	6000 K
Maxi SharXS HTI 1800 W	17.8 A		160000 lm	6500 K
Maxi SharXS HTI 2000 W	19 A		200000 lm	6500 K

Product description	Color rendering index Ra	Light center length (LCL)	Luminance	Luminous efficacy	Light center length (LCL) - (in)
Baby SharXS HTI 250 W/D5/80	> 85	35.0 mm	30000 cd/cm ²	75 lm/W	
Baby SharXS HTI 300 W/D5/57	80	35.0 mm	40000 cd/cm ²	65 lm/W	
Baby SharXS HTI 300 W/D5/65	85	35.0 mm	40000 cd/cm ²	75 lm/W	
Baby SharXS HTI 575 W/D5/56	85	35.0 mm	50000 cd/cm ²	75 lm/W	
SHARXS HTI 400 W/D3/75 ¹⁾	80	57.5 mm	55000 cd/cm ²		
SHARXS HTI 700 W/D4/60 ²⁾	> 80	57.5 mm	60000 cd/cm ²	85 lm/W	
SHARXS HTI 700 W/D4/75 ³⁾	> 80	57.5 mm	60000 cd/cm ²		
SHARXS HTI 1200 W/D7/60 ³⁾	85	57.5 mm	41000 cd/cm ²		
SharXS 1200W Brilliant ³⁾	94	57.5 mm	41000 cd/cm ²		
SHARXS HTI 1200 W/D7/75 ²⁾	80	57.5 mm	41000 cd/cm ²	90 lm/W	
SHARXS HTI 1500 W/D7/60 ⁴⁾	>80	57.5 mm	42000 cd/cm ²		
Maxi SharXS HTI 1800 W	90	90.0 mm			
Maxi SharXS HTI 2000 W	92	90.0 mm			3.54 in

Product family datasheet

Product description	Physical Attributes & Dimensions			
	Diameter (in)	Diameter	Diameter	Length
Baby SharXS HTI 250 W/D5/80	0.630 in	16.0 mm	16.0 mm	93.0 mm
Baby SharXS HTI 300 W/D5/57	0.630 in	16.0 mm	16.0 mm	93.0 mm
Baby SharXS HTI 300 W/D5/65	0.630 in	16.0 mm	16.0 mm	93.0 mm
Baby SharXS HTI 575 W/D5/56	1.024 in	16.0 mm	16.0 mm	93.0 mm
SHARXS HTI 400 W/D3/75 ¹⁾	0.709 in	18.0 mm	18.0 mm	136.0 mm
SHARXS HTI 700 W/D4/60 ²⁾	0.709 in	18.0 mm	18.0 mm	136.0 mm
SHARXS HTI 700 W/D4/75 ³⁾	0.709 in	21.0 mm	21.0 mm	136.0 mm
SHARXS HTI 1200 W/D7/60 ³⁾	0.866 in	21.0 mm	21.0 mm	136.0 mm
SharXS 1200W Brilliant ³⁾	0.866 in	21.0 mm	21.0 mm	136.0 mm
SHARXS HTI 1200 W/D7/75 ²⁾	0.866 in	21.0 mm	21.0 mm	136.0 mm
SHARXS HTI 1500 W/D7/60 ⁴⁾	0.984 in	24.5 mm	24.5 mm	136.0 mm
Maxi SharXS HTI 1800 W		30.5 mm	30.5 mm	220.0 mm
Maxi SharXS HTI 2000 W	1.102 in	30.5 mm	30.5 mm	220.0 mm

Product description	Product weight	Lamp base	Electrode gap (cold)	Operating Conditions
				Burning position
Baby SharXS HTI 250 W/D5/80	26.00 g	SFc10-4	5.0 mm	Any
Baby SharXS HTI 300 W/D5/57	25.00 g	SFc10-4	5.5 mm	Any
Baby SharXS HTI 300 W/D5/65	26.00 g	SFc10-4	5.5 mm	Any
Baby SharXS HTI 575 W/D5/56	26.00 g	SFc11-4	5.0 mm	Any
SHARXS HTI 400 W/D3/75 ¹⁾	30.00 g	SFc10-4	3.0 mm	Any
SHARXS HTI 700 W/D4/60 ²⁾	33.00 g	SFc10-4	4.0 mm	Any
SHARXS HTI 700 W/D4/75 ³⁾	33.00 g	SFc10-4	4.0 mm	Any
SHARXS HTI 1200 W/D7/60 ³⁾	33.00 g	SFc10-4	7.0 mm	Any
SharXS 1200W Brilliant ³⁾	33.00 g	SFc10-4	7.6 mm	Any
SHARXS HTI 1200 W/D7/75 ²⁾	33.00 g	SFc10-4	7.0 mm	Any
SHARXS HTI 1500 W/D7/60 ⁴⁾	35.00 g	SFc10-4	7.0 mm	Any
Maxi SharXS HTI 1800 W	104.00 g	SFc15.5	10.0 mm	Any
Maxi SharXS HTI 2000 W	104.00 g	SFc15.5	10.0 mm	Any

Product description	Cooling	Max. permitted ambient temp. pinch point	Maximum permitted pinch temperature	Lifetime Data
				Nominal lifetime
Baby SharXS HTI 250 W/D5/80	Forced ⁶⁾	450 °C ⁷⁾	450 °C	3000 hr
Baby SharXS HTI 300 W/D5/57	Forced ⁶⁾	450 °C ⁷⁾	450 °C	3000 hr
Baby SharXS HTI 300 W/D5/65	Forced ⁶⁾	450 °C ⁷⁾	450 °C	750 hr
Baby SharXS HTI 575 W/D5/56	Forced ⁶⁾	450 °C ⁷⁾	450 °C	500 hr
SHARXS HTI 400 W/D3/75 ¹⁾		450 °C	450 °C	1000 hr
SHARXS HTI 700 W/D4/60 ²⁾		450 °C ⁷⁾	450 °C	750 hr
SHARXS HTI 700 W/D4/75 ³⁾			450 °C	750 hr
SHARXS HTI 1200 W/D7/60 ³⁾			450 °C	750 hr
SharXS 1200W Brilliant ³⁾			450 °C	750 hr
SHARXS HTI 1200 W/D7/75 ²⁾	Forced ⁶⁾	450 °C ⁷⁾	450 °C	750 hr
SHARXS HTI 1500 W/D7/60 ⁴⁾			450 °C	750 hr

Product family datasheet

Product description	Cooling	Max. permitted ambient temp. pinch point	Maximum permitted pinch temperature	Lifetime Data
				Nominal lifetime
Maxi SharXS HTI 1800 W			450 °C	750 hr
Maxi SharXS HTI 2000 W			450 °C	750 hr

Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

Product description	Primary article identifier	Declaration no. in SCIP database	Candidate list substance 1
Baby SharXS HTI 250 W/D5/80	4008321129161	No declarable substances contained	No declarable substances contained
Baby SharXS HTI 300 W/D5/57	4008321129185	No declarable substances contained	No declarable substances contained
Baby SharXS HTI 300 W/D5/65	4008321129208	No declarable substances contained	No declarable substances contained
Baby SharXS HTI 575 W/D5/56	4008321129345	No declarable substances contained	No declarable substances contained
SHARXS HTI 400 W/D3/75 ¹⁾	4008321285157	No declarable substances contained	No declarable substances contained
SHARXS HTI 700 W/D4/60 ²⁾	4008321285218	No declarable substances contained	No declarable substances contained
SHARXS HTI 700 W/D4/75 ³⁾	4008321285232	No declarable substances contained	No declarable substances contained
SHARXS HTI 1200 W/D7/60 ³⁾	4008321285256	No declarable substances contained	No declarable substances contained
SharXS 1200W Brilliant ³⁾	4052899562622	No declarable substances contained	No declarable substances contained
SHARXS HTI 1200 W/D7/75 ²⁾	4008321285270	No declarable substances contained	No declarable substances contained
SHARXS HTI 1500 W/D7/60 ⁴⁾	4008321285294	No declarable substances contained	No declarable substances contained
Maxi SharXS HTI 1800 W	4062172399807	In work	
Maxi SharXS HTI 2000 W	4008321334947	No declarable substances contained	No declarable substances contained

¹⁾ Also available as an OEM package with 30 units without knurled nuts

²⁾ XS = eXtreme Seal (maximum permissible foil temperature 450 °C)

³⁾ Also available as an OEM package with 30 units without knurled nuts/XS = eXtreme Seal (maximum permissible foil temperature 450 °C)

⁴⁾ May be operated from 1,200...1,500 W

⁵⁾ Cold

⁶⁾ Fan

⁷⁾ Measured at Molybdenum foil / Pinch Seal region (eXtreme Seal Technology)

Product family datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Maxi SharXS HTI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.