Product family datasheet

OSRAM

Lightbar VX250-SP



ECE certified - ECE R112 The necessary tests and approvals were carried out and an ECE type approval was granted2)ECE reference number: 30



Spot Beam Designed for far field illumination. For a focused illumination in the far field of the vehicle with a light beam up to 318 m length.See and be seen with OSRAM



Slim design Slim design for a discreet appearance when mounted on the vehicle



on-road & off-road Versatile applicable and flexible in use.On-road & offroad, in terrain, at work and in the spare time.



Bringing light to life with OSRAM LEDriving driving and working lights

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Lightbar VX250-SP. With its 9 powerful, high-performance long-life LEDs, the OSRAM LEDriving Lightbar VX250-SP has a range of up to 318 meter and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the OSRAM LEDriving Lightbar VX250-SP with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 1500 lumens of luminosity scores with highest optical efficiency and homogeneous light distribution. This results in the possibility of an improved view for you and the improved visibility of your vehicle by other road users, and consequently also increased safety on-road and off-road.Whether on-road or off-road - The OSRAM LEDriving Lightbar VX250-SP impresses with its powerful performance and a long service life with up to 5000 hours. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The OSRAM LEDriving Lightbar VX250-SP has been tested and validated with the IP-Protection Class IP67 in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. The integrated driver and the thermal management system regulate the temperature of the LED Lightbar and can thus prevent damage from overheating. The polarity protection inhibits the wrong polarity of the voltage supply and can thus prevent possible damage by automatically switching off the LEDs. On-road and off-road, the OSRAM LEDriving Lightbar VX250-SP is an effective and efficient addition to your vehicle. No registration or entry in the vehicle documents is necessary for these ECE-certified LED driving lights2).ECE reference number: 30The OSRAM LEDriving Lightbar VX250-SP can be attached to cars, trucks, agricultural machinery, farm machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and guads2). The OSRAM LEDriving VX250-SP is versatile applicable and flexible in use.2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

Product family datasheet

Technical data

	Product infor	mation	EL	ectrical data			Photomet rical data
Product description	Order reference	Application (and Product			Nominal vattage	Test voltage	Luminous flux
Lightbar VX250-SP ¹⁾	LEDDL115- SP	Additional hi application	gh beam 12	2/24 V 2	2700 W	13.2 V	1500 lm
	LED module information	Lifespan	Capabilities	Certificat standards		Logistic	al data
Product description	Number of LEDs per module	Lifespan Tc	Technology	ECE refer number	ence	Commo	dity code
Lightbar VX250-SP ¹⁾	9	5000 h	LED ²⁾	30		851220	00900
	Environmenta Information a		33 of EU Regul	lation (EC) 19	07/2006 (REACh)	
Product description	Date of Decla	Date of Declaration Prima Identi			idate List tance 1	CA: 1	S No. of substance
Lightbar VX250-SP ¹⁾	28-02-2024	40	62172141888	Lead		74	39-92-1

Product description	Safe Use Instruction	Declaration No. in SCIP database
Lightbar VX250-SP ¹⁾	The identification of the Candidate List substance is sufficient to allow safe use of the article.	652f9f13-bd88-4af1- b0f4-85104cea2091

¹⁾ Beam Pattern: Spot

²⁾ Light-emitting diode application

Product family datasheet

Download Data

	File
Z	User instruction LEDriving Lightbar VX250-SP SR
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application Working and Driving Lights Amarok Winter
D	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
D	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
D	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
D	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
Ŀ	360 Degree Image LEDriving Lightbar VX250-SP LEDDL115-SP

The installation of the OSRAM LEDriving Lightbar VX250-SP is fully ECE compliant and therefore registration free. This does not include individual custom requirements of countries, in addition to the standardized ECE certification of the product.

1) Precise terms and conditions at: www.osram.com/am-guarantee

2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

Refer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.