

LFP1100TW-G5 -825.940-09 L2

LINEARlight FLEX Tunable White Protect | LED modules for professional and industrial applications



Product family features

- 24 V LED strips flexible and cuttable
- Luminous flux: up to 3,400 lm/m
- Up to 60,000 h L90/B10 with SDT technology, tested acc. to IEC 62717 on real LED strips
- Adjustable color temp. via Tunable White: 2500...4000 K, 2700...5700 K CRI90
- CRI 90 versions available
- Stable light flux over length: active constant current regulators (ICs), PWM safe
- Embedded automatic quick protection against accidental miswiring up to 25 V
- Fully PWM dimmable from zero up to 2.5 kHz, audible noise free, suitable for quite places
- IP67 & IP66
- Salt-mist atmosphere resistant (acc. to IEC 60068-2-52, highest severity)
- UV radiation resistant (acc. to ISO 4892-2) / Mixed flowing gas corrosion resistant (IEC 60068-2-60)
- Designed, engineered and manufactured and tested in Italy (ISO9001, ISO 17025, ACCREDIA, VDE)

Product family benefits

- Color uniformity better than 3 SDCM on the entire LED strip and between strips
- LED lifetime acc.to IES LM-80 and IES TM-21 standards, and also internal OSRAM LAB tests
- Excellent robustness: single reel manufacturing technology (no solder joints on strip)
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
- Extraordinary design and high quality materials



Technical data


Electrical data

Nominal voltage	24.0 V
Type of current	DC
Nominal wattage per meter	9.9 W
Rated wattage	88.70 W
Input voltage range	23...25 V
Accidental reverse input voltage protection up to	25 V

Photometrical data

Light color LED	Dynamic White
Color temperature	2500...4000 K
Color rendering index Ra	80
Luminous flux per meter	1156 lm
Luminous efficacy	117 lm/W
Standard deviation of color matching	≤3 sdc _m
Light color (designation)	2500...4000 K
Rated color temperature	3100 K

Dimensions & weight



Length	9000 mm
Cable length	500.0
Product weight	519.00 g
Cable cross-section, input side	0.5 mm ²
Width	11.1 mm
Height	4.50 mm

Temperatures & operating conditions

Product datasheet

Temperature range in operation at Tc point	-30...80 °C ¹⁾
Temperature range at storage	-40...85 °C

¹⁾ Exceeding the maximum ratings will reduce expected life time or destroy the LED strip.

Additional product data

ID of contained light source	LS_TRV_286105
------------------------------	---------------

Certificates & standards

Standards	CE/UL/ENEC/EAC
Energy efficiency class of the contained light source	F

Logistical data

Commodity code	85395100000
----------------	-------------







Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4062172196567
Declaration No. in SCIP database	In work



Equipment / Accessories

- Flexessories: a complete set of aluminum channels with diffusers and lenses
- Drivers and dimmers: wide selection of OPTOTRONIC 24 V DALI, DMX and BLE
- Check for more detailed information the specification sheets in the download section

Download Data

File	
	User instruction LINEARlight FLEX Protect Tunable White
	Product Datasheet LINEARlight Flex Protect Tunable White CRI90 specification sheet (EN)
	Brochures Light is freedom of design (EN)
	Certificates VDE ENEC CERTIFICATE 40052516 160823
	Certificates LF(P) TW G5 CB 180121
	Declarations of conformity Flex Protect TW G2 CE 4264939 180823

Product datasheet

	Eulumdat LFP1100TW-G5-825.940-09 L2 LTD 130421
	IES data LFP1100TW-G5-825.940-09 L2 IES 130421

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172196567	LFP1100TW-G5 - 825.940-09 L2	Shipping carton box 8	365 mm x 286 mm x 366 mm	38.21 dm ³	8370.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Accessories Optional

Product description	Accessory name	Accessory code
LFP1100TW-G5 -825.940-09 L2	FX-QMW-G1 -TU26H25-300	▶ 4052899448803
LFP1100TW-G5 -825.940-09 L2	FX-QMS-G1 -TU15H6-300	▶ 4052899448865
LFP1100TW-G5 -825.940-09 L2	FX-QMS-G1 -TU15H6W3-300	▶ 4052899448889
LFP1100TW-G5 -825.940-09 L2	FX-QMS-G1 -TU16H12W3-300	▶ 4052899448988
LFP1100TW-G5 -825.940-09 L2	FX-QMS-G1 -TU16H12-300	▶ 4052899448964

LFP1100TW-G5 -825.940-09 L2	FX-QMS-G1 -TU16H12LS-300	▶ 4052899449046
-----------------------------	--------------------------	-----------------

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.