

# **TEC Flex Protect IP66 Connector**

## Accessories for Flexible LED strips



- Quick and easy installation
- Compatible with Linearlight Flex
- Compatible with TEC Flex



#### Product family benefits

- Simple installation, no tools or soldering required (CONNECTsystem)
- Reduced installation time (CONNECTsystem)
- Can be connected to the front of the module or at division points (CONNECTsystem)
- Low profile (CONNECTsystem)


## Product family datasheet


#### Technical data

	Dimensions & weight		Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Length	Product weight	Commodity code	Date of Declaration
FX -SC08-G2-CT4PJ	9.0 mm	0.80 g	85366990990	30-08-2022

Product description	Primary Article	Candidate List	Declaration No. in
	Identifier	Substance 1	SCIP database
FX -SC08-G2-CT4PJ	4052899464858	No declarable substances contained	No declarable substances contained


## Product family datasheet





729184\_ACC LECV LF B2B Conn. 12,7 5 3 G2

729196\_ACC LECV LF B2B Conn. 12,7 5 3 G2



#### 729327\_FX-SC08-G2\_CT4PJ 50XFS25

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Sales and Technical Support

Sales and Technical Support www.osram.com

#### Download Data

	File
*	User instruction Connection System for LINEARlight Flex & TEC Flex IP00
*	Product Datasheet 726951_SLIMCONNECT SYSTEM 08 G2

### Product family datasheet

Brochures

7

Light is freedom of design (EN)

#### Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899464858	FX -SC08-G2-CT4PJ	Shipping carton box 1250	510 mm x 340 mm x 315 mm	54.62 dm³	3914.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.