

# LS/PD MULTI3 CI

LS/PD MULTI 3 CI | Sensors for light management systems



#### Product family features

- Ceiling installation sensor with moveable sensor head
- Connection via four-pole screw terminal or modular 4c4pconnector

# Product family benefits


- Particularly small construction

# Areas of application

- Offices
- Corridors
- Classrooms
- Training rooms
- Stairways
- Sanitary areas

#### Technical data

# **Dimensions & weight**



Length	500 mm
Width	500 mm
Height	250 mm
Product weight	3000 g
Diameter	500 mm

# Temperatures & operating conditions

Ambient temperature range	0+50 °C

# Certificates & standards

Type of protection	IP20
. ype o. p. occor.	20

# Logistical data

Commodity code	85365019900
----------------	-------------

# **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	29-06-2022	
Primary Article Identifier	4008321916648	
Declaration No. in SCIP database	In work	

# Product datasheet

#### Equipment / Accessories

- Surface mounting in connection with SENSOR KIT
- Suitable for MULTIeco, DIM MULTIeco, DALI MULTIeco control unit
- Suitable for DALI Professional Sensor Coupler

#### Download Data

# File Declarations of conformity 334067\_LMS MULTI3 SENSORS Installation/Operation notice 334180\_LSPD MULTI 3 CI light and presence sensor for ceiling installation

# Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321916648	LS/PD MULTI3 CI	Shipping carton box 10	190 mm x 164 mm x 184 mm	5.73 dm <sup>3</sup>	565.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.