

DALI COUPLER E G2

DALI COUPLER E G2 | Sensors



Product family features

- Coupler for integration of light and presence information in DALI installations
- Switching input for motion detector (potential free)
- Analog input (0-10 V) for light sensor

Product family benefits

- DALI-2 certified
- Output for presence detection feedback LEDs
- 24 V DC output for power supply of external sensors

Areas of application

- Installation in industry and office luminaires
- Suitable for luminaire integration
- Corridors
- Warehouses


Product datasheet

Technical data


Electrical data

| System wattage | 0.30 W |
|---------------------------------|----------|
| Nominal voltage | 220240 V |
| Mains frequency | 50/60 Hz |
| Required DALI current (typical) | 2 mA |
| Peak DALI current | 2 mA |
| Maximum start-up time (DALI) | 600 ms |

Dimensions & weight







| Length | 118.0 mm |
|----------------|----------|
| Width | 30.0 mm |
| Height | 21.0 mm |
| Product weight | 50.00 g |

Colors & materials

| Product color Light gre | у |
|-------------------------|---|
|-------------------------|---|

Temperatures & operating conditions

Capabilities

| Dimming interface | DALI-2 |
|---------------------------|---|
| Number of control outputs | 1 |
| Type of installation | Ceiling integration/Luminaire integration |
| Control interface | DALI |

Certificates & standards

Product datasheet

| Type of protection | IP20 |
|--------------------|------|
| • | |

Logistical data

| Commodity code | 85371098990 |
|----------------|-------------|
| Commodity code | 033/1070770 |

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | |
|---|--|--|
| Date of Declaration | 04-10-2023 | |
| Primary Article Identifier | 4062172072212 | |
| Candidate List Substance 1 | Lead | |
| CAS No. of substance 1 | 7439-92-1 | |
| Safe Use Instruction | The identification of the Candidate List substance is sufficient to allow safe use of the article. | |
| Declaration No. in SCIP database | 6543caa2-cff3-45b3-845d-46f487d939db | |

Equipment / Accessories

- Ceiling or independent installation via ECO CI KIT possible
- Suitable for external light and presence sensors

Download Data

| | File |
|---|--|
| 大 | User instruction DALI2 COUPLER E |
| Z | Declarations of conformity DALI G2 Sensor Coupler CE 4202657 03 060823 |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4062172072212 | DALI COUPLER E G2 | Shipping carton box 25 | 200 mm x 140 mm x 147 mm | 4.12 dm ³ | 1820.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Accessories Optional

Product datasheet

| Product description | Accessory name | Accessory code |
|---------------------|----------------|----------------|
| DALI COUPLER E G2 | ECO CI KIT | 4008321392091 |

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.