Product datasheet



LS/PD MULTI3 CI

LS/PD MULTI 3 CI | Sensors for light management systems



Product family features

- Ceiling installation sensor with moveable sensor head
- Connection via four-pole screw terminal or modular 4c4pconnector

Product family benefits

- Particularly small construction

Areas of application


- Offices
- Corridors
- Classrooms
- Training rooms
- Stairways
- Sanitary areas

LS/PD MULTI3 CI

Product datasheet

Technical data

Dimensions & weight



Width	500 mm
Height	250 mm
Product weight	3000 g
Diameter	500 mm

Temperatures & operating conditions

Ambient temperature range	0+50 °C

Capabilities

Type of installation	On-top ceiling mounting/Ceiling integration

Logistical data

Commodity code

85365019900

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	29-06-2022		
Primary Article Identifier	4008321916648		
Declaration No. in SCIP database	In work		

Equipment / Accessories

- Surface mounting in connection with SENSOR KIT
- Suitable for MULTIeco, DIM MULTIeco, DALI MULTIeco control unit
- Suitable for DALI Professional Sensor Coupler

LS/PD MULTI3 CI

Product datasheet

Download Data

	File
*	Declarations of conformity 334067_LMS MULTI3 SENSORS
7	Installation/Operation notice 334180_LSPD MULTI 3 CI light and presence sensor for ceiling installation

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321916648	LS/PD MULTI3 CI	Shipping carton box 10	190 mm x 164 mm x 184 mm	5.73 dm³	565.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.