

DALI SWITCH SO

DALI Switch SO | Signal converters for LMS




Product family features

- DALI-controlled switch output for incandescent lamps, QT, OT, PT, HT control gear
- 3 independent relay contacts
- Load capacity of switching contact: 6 A ohmic load
- Supply voltage: 24 V DC
- Floating contacts

Technical data

Dimensions & weight



Height	62.0 mm
Product weight	155.00 g

Temperatures & operating conditions

Ambient temperature range	0...+45 °C
---------------------------	------------

Capabilities

Type of installation	DIN rail mounting
----------------------	-------------------

Logistical data

Commodity code	85371098990
----------------	-------------

Environmental information



Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-05-2023
Primary Article Identifier	4008321533364
Candidate List Substance 1	Lead titanium zirconium oxide
CAS No. of substance 1	12626-81-2
Candidate List Substance 2	Lead
CAS No. of substance 2	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	39deb6b7-0480-43a6-bbff-c8d3352282ce

Product datasheet

Equipment / Accessories

- Can be used with all DALI control units
- 24 V supply required (e. g. PS 30)

Download Data

File	
	User instruction DALI SWITCH SO UI G10604058 241122
	Declarations of conformity 334856_Declaration of conformity – DALI SWITCH SO

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321533364	DALI SWITCH SO	Shipping carton box 8	250 mm x 208 mm x 89 mm	4.63 dm ³	1434.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.