Product datasheet

LEDinspect UTILITY1000

Inspectionlights



Multi-Functional Lamp

High flexibility and diverse adjustment possibilities. Up to 180° ratcheting bases and up to 360° rotating body.

1000 lm

2 light functions: Up to 1000lm-high Up to 400lm-low For individually adjustable light settings

Magnetic Base & Rotatable Hook

Versatile mounting options

2-year-OSRAM guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Light is versatile

Designed with versatility in mind, the UTILITY 1000 combines magnetic, 180° ratcheting base with a 360° rotating body. This means the inspectionlight can be used either freestanding or hands-free, positioned in any number of ways to ensure the work area is properly illuminated. With two light functions - high with up to 1000lm and low with up to 400lm - it produces a light output that can be matched to the task at hand.

This inspection light is ideal as a light for manual work, car repairs and everyday use. OSRAM also provides a 2-year guarantee on this product* Charging cable and mains

© 2026, OSRAM GmbH. All rights reserved.

charger included.

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	LED inspection lights

General Product Information

Global order reference	LEDIL407

Electrical Data

Nominal wattage	19 W
Nominal voltage	7.4 V

Photometric Data

Color temperature	6500 K
Nominal luminous flux	1000 lm
Light color LED	White

Physical Attributes & Dimensions



Product weight	490.00 g
Length	500.0 mm
Width	41.0 mm
Height	48.0 mm

LED module information

Number of LEDs per module	1

Colors & materials

Base color	Black / Orange

© 2026, OSRAM GmbH. All rights reserved.

Lifetime Data

Guarantee	2 years

Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes
Battery	High-quality lithium-ion battery

Capabilities

Technology	LED

Certificates & standards

Standards	CE / EMC / MSDS / ROHS
IK Class	IK07

Logistical data

Watt hour per battery	9.62

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	12140b2a-ec70-4b9c-9c15-9b33a359d5fe

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172338356	INSPECTION LAMP	Folding carton box 1	80 mm x 57 mm x 510 mm	2.33 dm^3	583.00 g
4062172338363	INSPECTION LAMP	Shipping carton box 6	530 mm x 190 mm x 188 mm	18.93 dm^3	3968.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

© 2026, OSRAM GmbH. All rights reserved.

Download Data

	File
	User instruction LEDinspect UTILITY 1000 LEDIL407
	User instruction GPRS_Safety symbols instructions

Legal advice
Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.