OSRAM

LEDinspect POCKET200

Inspectionlights





Multi-Angle positioning 180° flex and 360° twist. Extra slim design



200 Lumen
3 light functions: Up to 200lm-high Up
to 80lm-low Up to 40lm-torchlight



2-year OSRAM Guarantee

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Light is versatile

This high-quality inspection light from OSRAM is perfect for professional and private use. With three light functions - high with up to 200lm, low with up to 80lm and torch function with up to 40lm - there is the right light output for the task at hand. The compact design combined with multiangle positioning -180° flex and 360° rotation- gives maximum flexibility and adjustability to give light exactly where needed. The integrated charge indicator shows the charging status of the rechargeable battery - up to 1,5 h operating time for high power or up to 3h for low power. This inspection light also contains magnets for hands-free work and easy attachment and is therefore ideal as a light for manual activities, car repairs and in everyday life. In addition, OSRAM grants a 2-year guarantee on this

| Proc | luct fai | mily d | latasl | heet |
|------|----------|----------|--------|------|
| FIUU | iuct iai | ιιιιιν υ | ıatası | וככנ |

product*

Product family datasheet

Technical data

| | Product information | General Prod Information | uct | Electrical Dat | a | |
|---------------------|---|-----------------------------|--------------------|---|---------------------|--|
| Product description | Application (Category and Product specific) | Global order reference | | Nominal watt | age | Nominal voltage |
| INSPECTION LAMP | LED inspection lights | LEDIL408 | | 2 W | | 3.7 V |
| | Photometric Data | | | | Physica Dimen | al Attributes & sions |
| Product description | Color temperature | Nominal lum flux | inous | Light color LED | Produc | ct weight |
| INSPECTION LAMP | 6200 K | 200 lm | | White | 120.00 |) g |
| | | | | | | LED module information |
| Product description | Length | Width | | Height | | Number of LEDs per module |
| INSPECTION LAMP | 267.0 mm | 40.0 mm | | 42.0 mm | | 2 |
| | Colors & materials | Lifetime Data | Addition | al product data | | |
| Product description | Base color | Guarantee | Type of | Battery | Number batteries | of included s |
| INSPECTION LAMP | Black / Orange | 2 years | Recharg | eable | 1 | |
| | | Capabilities | Certific standa | ates & | Logisti | ical data |
| Product description | Scope of battery | Technology | IK Clas | S | Watt h | our per battery |
| INSPECTION LAMP | Yes | LED | IK07 | | 2.96 | |
| | Environmental & Regul | | | (EC) 1907/2006 | 6 (REACh) |) |
| Product description | Candidate list substance 1 | CAS No. of su | bstance | Safe use instr | uction | Declaration no. in SCIP database |
| INSPECTION LAMP | Lead | 7439-92-1 | | The identificathe Candidate substance is sufficient to a safe use of tharticle. | e List allow | fd47c268-ee86- 4581-a702- e67ef0854f7a |

Product family datasheet

Download Data

| | File |
|----------|---|
| Z | User instruction GPRS_Safety symbols instructions |
| X | User instruction LEDinspect POCKET 200 |
| D | Movie application LEDinspect Inspection Lights Trailer |

Legal advice

Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.