

LEDinspect MINI250

Inspectionlights




Multi-Angle Light Output
High flexibility and diverse adjustment possibilities thanks to multi angle positioning



250 Lumen
3 light functions: Up to 250lm -high Up to 130lm - low Up to 70lm -torchlight



USB-Cable & Power Plug
Rechargeable battery. USB charging cable and power plug are included in the scope of supply



2-year-OSRAM guarantee*
Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Product datasheet



Light is versatile

This high-quality inspection light from OSRAM is perfect for professional and private use. With three light functions - high with up to 250lm, low with up to 130lm and torchlight function with up to 70lm, there is a light output to suit the task at hand. The 180° flex base gives further flexibility to be able to adjust the lightbeam where needed. The inspection light is rechargeable, and the integrated charge level indicator shows the current status of the battery with up to 3h operating time at high power or up to 6h at low power. A USB Type-C charging cable and the corresponding power adaptor are included in the scope of supply. In accordance with IP65 protection rating, this inspection light has protection against dust and water ingress and is tested for impact resistance in accordance with IK07. This LED light is easy to carry, has a non-slip and dirt-repellent surface, includes an integrated hook & magnets for hands-free work and easy attachment, making it ideal for craft activities, car repairs and in everyday life. In addition, OSRAM provides a 2-year guarantee on this product*

Product datasheet

Technical data

Product information

Application (Category and Product specific)	LED inspection lights
---	-----------------------

General Product Information

Global order reference	LEDIL401
------------------------	----------

Electrical Data

Nominal wattage	7 W
Nominal voltage	3.7 V

Photometric Data

Color temperature	5700 K
Nominal luminous flux	250 lm
Light color LED	White

Physical Attributes & Dimensions

Product weight	215.00 g
Length	200.0 mm
Width	56.0 mm
Height	41 mm

LED module information

Number of LEDs per module	2
---------------------------	---

Colors & materials

Base color	Black / Orange
------------	----------------

Lifetime Data

Guarantee	2 years
-----------	---------

Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes
Battery	High-quality lithium-ion battery

Capabilities

Product datasheet

Technology	LED
------------	-----

Certificates & standards

Standards	CE / EMC / MSDS / ROHS
IK Class	IK07

Logistical data

Watt hour per battery	10.00
-----------------------	-------

Environmental & Regulatory Information



Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	05-08-2024
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	94ddcbeb-ba73-4700-a565-7ccc51aa1508

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899623828	INSPECTION LAMP		- x - x -	0.95 dm ³	
4052899623941	INSPECTION LAMP	Shipping carton box 6	- x - x -	8.16 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 User instruction LEDinspect MINI 250
 Movie application LEDinspect Inspection Lights Trailer

Legal advice

Application advice:

Product datasheet

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.