Product datasheet

OSRAM

COOL BLUE INTENSE (NEXT GEN) W5W

Extra white light for LED look



Extra white light for stylish LED look

Up to 4,000 Kelvin

High contrast and brilliantly white light for most stylish and modern look on the road



The extra white light with up to 4,000 K

COOL BLUE INTENSE signal lamps stand out through their stylish appearance. Their bluish-white light with a color temperature up to 4,000 K provides a cool xenon-like look. The lamps can be used for number plate lights as well as for position and parking lights.

Product datasheet

Technical data

Product information

Order reference	2825CBN
Application (Category and Product specific)	Auxiliary lamp

Electrical data

Power input	5.5 W
Nominal voltage	12.0 V
Nominal wattage	5.00 W
Power input tolerance	±10 %
Test voltage	13.5 V

Photometrical data

Color temperature	3700 K
Luminous flux	50 lm
Luminous flux tolerance	±20 %

Dimensions & weight

Length	25.1 mm
Diameter	10.0 mm
Product weight	1.50 g

Lifespan

Lifespan B3	375 h
Lifespan Tc	750 h

Additional product data

Base (standard designation)	W2.1x9.5d
•	

Capabilities

Technology	AUX ¹⁾

¹⁾ Auxiliary signal lamp

Certificates & standards

ECE category	W5W
--------------	-----

Country specific categorizations

Order reference	2825CBN
-----------------	---------

Product datasheet

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration	07-03-2024			
Primary Article Identifier	4062172215060 4062172218740 4062172218726 4062172394710			
Candidate List Substance 1	No declarable substances contained			
Declaration No. in SCIP database	In work			

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172215060	COOL BLUE INTENSE (NEXT GEN) W5W	Blister 2	135 mm x 95 mm x 13 mm	0.17 dm ³	14.00 g
4062172215077	COOL BLUE INTENSE (NEXT GEN) W5W	Shipping carton box 20	140 mm x 105 mm x 146 mm	2.15 dm ³	189.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

