Product family datasheet



# Lightbar VX1000-CB SM





#### Double ECE-Certification - 2 x ECE R112

The necessary tests and approvals were carried out and an ECE type approval was granted2)Central single mount possibleECE reference number: 37.5 + 37.5



**Combo Beam** 

Designed for both: far-field and near-field illumination. For widespread illumination in the near field and spot illumination in the far field.



Up to 525m long light beam

See and be seen with OSRAM.Special curved reflector design with extraordinary perforation.



**On-road & Off-road** 

Versatile applicable and flexible in use.On-road & offroad, in terrain, at work and in the spare time.



# Bringing light to life with OSRAM LEDriving driving and working lights

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Lightbar VX1000-CB SM. With its 36 powerful, high-performance OSRAM long-life LEDs, the VX1000-CB SM has a range of up to 525 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the OSRAM LEDriving Lightbar VX1000-CB SM with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 6000 lumens of luminosity scores with

highest optical efficiency and homogeneous light distribution. This results in the possibility of an improved view for you and the improved visibility of your vehicle by other road users, and consequently also increased safety on-road and off-road.

Whether on-road or off-road - The OSRAM LEDriving Lightbar VX1000-CB SM impresses with its powerful performance and a long service life with up to 5000 hours. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The OSRAM LEDriving Lightbar VX1000-CB SM has been tested and validated with the IP-Protection Class IP67 in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. The integrated driver and the thermal management system regulate the temperature of the LED Lightbar and can thus prevent damage from overheating. The polarity protection inhibits the wrong polarity of the voltage supply and can thus prevent possible damage by automatically switching off the LEDs. On-road and off-road, the OSRAM LEDriving Lightbar VX1000-CB SM is an effective and efficient addition to your vehicle. No registration or entry in the vehicle documents is necessary for these ECE-certified LED driving lights<sup>2)</sup>

ECE reference number: 37.5 + 37.5

The OSRAM LEDriving Lightbar VX1000-CB SM can be attached to cars, trucks, agricultural machinery, farm machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads <sup>2)</sup>

The OSRAM LEDriving Lightbar VX1000-CB SM is versatile applicable and flexible in use.

2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

# Product family datasheet

# Technical data

	Product information Application (Category and Product specific)		General Pro	Electrical Data				
Product description			Global orde reference	Nominal voltage			Nominal wattage	
Lightbar VX1000-CB SM <sup>1)</sup>	Additional I application	Additional high beam application		LEDDL120-CB SR		12/24 V		108 W
		Photomet	tric Data LED modu informatio				Capabilities	
Product description	Test voltage	Nominal l flux	uminous	Number of LEDs per module		Lifespan Tc	Technology	
Lightbar VX1000-CB SM <sup>1)</sup>	13.2 V	6000 lm		36		5000 hr	LED	2)
Product description	Certificates Approval m		s Type of prote	ection	Stand	ards		ECE reference
Lightbar VX1000-CB SM <sup>1)</sup>		E57 approval		 IP67		2x ECE R112 / R10		number 37.5 + 37.5
		Logistical data Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) (REACh)				(EC) 1907/2006		
Product description	Commodity	Commodity code		Candidate list substance 1		CAS No. of substance 1		Safe use instruction
Lightbar VX1000-CB SM <sup>1)</sup>	851220009	85122000900		Lead		7439-92-1		The identification of the Candidate List substance is sufficient to allow safe use of the article.

Product description	Declaration no. in SCIP database	
Lightbar VX1000-CB SM <sup>1)</sup>	d05be9e0-c08f-48c6- a54d-36640953ffa9	

<sup>1)</sup> Beam Pattern: Combo

 $^{2)}$  Light-emitting diode application

# Product family datasheet

### Download Data

	File
Z	User instruction GPRS_Safety symbols instructions
Z	Brochures OSRAM Lightbar VX1000-CB SM Flyer (DE)
7	Brochures OSRAM Lightbar VX1000-CB SM Flyer (EN)
D	Video Video OSRAM LEDriving driving & working
D	Video Product Video OSRAM LEDriving Lightbar VX1000-CB SM

## Legal advice

Legal advice:The installation of the OSRAM LEDriving Lightbar VX1000-CB SM is fully ECE compliant and therefore registrationfree. This does not include individual custom requirements of countries, in addition to the standardized ECE certification of the product. <sup>1)</sup> Precise terms and conditions at: www.osram.com/am-guarantee<sup>2)</sup>OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.Refer to www.osram.com/am-guarantee for precise conditions

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.