## **OSRAM**

# LEDriving SL T5

Ideal replacement for any vehicle



Suitable for various vehicle interior and exterior applications

Available in Cool White

Replaces conventional T5 lamps (e.g. ECE W2.3W)

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for T5 (e.g W2.3W)

LEDriving SL T5 replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional T5 lamp bases (e.g. ECE W2.3W). In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

### Product family datasheet

#### Technical data

|                           | Product information |                                               |                                                | Electrical data |                    |                    |
|---------------------------|---------------------|-----------------------------------------------|------------------------------------------------|-----------------|--------------------|--------------------|
| Product description       | Order<br>reference  | Product<br>type (off-<br>road vs.<br>on-road) | Application (Category and Product specific)    | Power<br>input  | Nominal<br>voltage | Nominal<br>wattage |
| LEDriving SL ≜ W2.3W (T5) | 2723DWP             | Off-road ≙<br>W2.3W (T5)                      | Mainly used for signal/ indicator applications | 0.25 W          | 12.0 V             | 0.25 W             |

|                     |                            |                 | Photomet rical data | Dimensions & weight |          | Lifespan       |                |
|---------------------|----------------------------|-----------------|---------------------|---------------------|----------|----------------|----------------|
| Product description | Power<br>input<br>toleranc | Test<br>voltage | Luminous<br>flux    | Length              | Diameter | Lifespan<br>B3 | Lifespan<br>Tc |
|                     | е                          |                 |                     |                     |          |                |                |
| LEDriving SL        | ±20 %                      | 13.5 V          | 25 lm               | 16.5 mm             | 6 mm     | 750 h          | 2000 h         |

|                     | Additional product data           | Capabilities      | Environmental information<br>Information according Art. 33 of EU<br>Regulation (EC) 1907/2006 (REACh) |                                  |
|---------------------|-----------------------------------|-------------------|-------------------------------------------------------------------------------------------------------|----------------------------------|
| Product description | Base<br>(standard<br>designation) | Technology        | Date of Declaration                                                                                   | Primary Article<br>Identifier    |
| LEDriving SL        | W2x4.6d                           | LED <sup>1)</sup> | 07-03-2024                                                                                            | 4062172254687  <br>4062172401838 |

| Product description       | Declaration No. in SCIP database |
|---------------------------|----------------------------------|
| LEDriving SL ≙ W2.3W (T5) | In work                          |

 $<sup>^{1)}</sup>$  Light-emitting diode lamp

#### Product family datasheet

#### Download Data

#### File



**Brochures** 

LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.