OSRAM

LEDriving SL T5

Ideal replacement for any vehicle



Suitable for various vehicle interior and exterior applications

Available in Cool White

Replaces conventional T5 lamps (e.g. ECE W2.3W)

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for T5 (e.g W2.3W)

LEDriving SL T5 replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional T5 lamp bases (e.g. ECE W2.3W). In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

Order reference	2723DWP	
Product type (off-road vs. on-road)	Off-road ≙ W2.3W (T5)	
Application (Category and Product specific)	Mainly used for signal/ indicator applications	


Electrical data

Power input	0.25 W
Nominal voltage	12.0 V
Nominal wattage	0.25 W
Test voltage	13.5 V
Power input tolerance	±20 %

Photometrical data

Luminous flux	25 lm
Luminous flux tolerance	±25 %
Color temperature	6000 K
Light color LED	Cool white

Dimensions & weight



Diameter	6 mm
Product weight	0.35 g
Length	16.5 mm

Lifespan

Lifespan B3	750 h
Lifespan Tc	2000 h
Guarantee	4 years

Product datasheet

Additional product data

Capabilities

¹⁾ Light-emitting diode lamp

Country specific categorizations

Order reference	2723DWP
-----------------	---------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	07-03-2024		
Primary Article Identifier	4062172254687 4062172401838		
Declaration No. in SCIP database	In work		

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172254687	LEDriving SL ≙ W2.3W (T5)	Blister 2	135 mm x 95 mm x 8 mm	0.10 dm ³	12.00 g
4062172254694	LEDriving SL ≙ W2.3W (T5)	Shipping carton box 10	104 mm x 71 mm x 146 mm	1.08 dm³	93.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File

Brochures
LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

Product datasheet

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

