OSRAM

LEDriving HLM EASY HS1



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



Superior brightness

Allowing a high compatibility and an easy installation.



LED replacement for conventional HS1 high and low beam lamps

Reduced glaring thanks to an optimal light distribution



LED high and low beams lamps with plug & play system for motorcycles.

The OSRAM LEDriving HLM EASY represent an easy solution to upgrade conventional motorcycle headlights with cool white LED light – with a color temperature of 6,000 K, they provide a stylish and modern look as well as superior brightness. Equipped with the latest LED technology and a very compact design, these lamps allow high compatibility and an easy installation for a wide range of motorcycle models. The LEDriving HLM EASY lamps are 12V and AC/DC compatible and offer a long service life. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

| Order reference | 64185DWESY | |
|---|--|--|
| Product type (off-road vs. on-road) | Off-road ≙ HS1 | |
| Application (Category and Product specific) | Mainly used for headlight applications | |


Electrical data

| Power input | 6.0 W / 5.0 W |
|-----------------------|---------------|
| Nominal voltage | 12.0 V |
| Nominal wattage | 5/5 W |
| Test voltage | 13.2 V |
| Power input tolerance | ±10 % |

Photometrical data

| Luminous flux | 650/500 lm | |
|-------------------------|------------|--|
| Luminous flux tolerance | ±15 % | |
| Color temperature | 6000 K | |
| Light color LED | Cool white | |

Dimensions & weight



| Length | 88.0 mm |
|----------------|---------|
| Diameter | 21.0 mm |
| Product weight | 33.00 g |

Lifespan

| Lifespan B3 | 500 h |
|-------------|--------|
| Lifespan Tc | 1000 h |

Product datasheet

Additional product data

| Base (standard designation) | PX43t |
|-----------------------------|-------|
|-----------------------------|-------|

Capabilities

| Technology | LED |
|------------|-----|
|------------|-----|

Country specific categorizations

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | |
|---|-------------------------------|--|--|--|
| Date of Declaration 08-03-2024 | | | | |
| Primary Article Identifier | 4062172345521 4062172399869 | | | |
| Declaration No. in SCIP database In work | | | | |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4062172345521 | LEDriving HLM EASY | Blister 1 | 135 mm x 95 mm x 51 mm | 0.65 dm ³ | 44.00 g |
| 4062172345538 | LEDriving HLM EASY | Shipping carton box 5 | 154 mm x 113 mm x 145 mm | 2.52 dm ³ | 319.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

