

# OPTOTRONIC Wireless Intelligent - QBM NFC L (SELV)

Linear constant current LED driver - Dimmable



## Areas of application

- Linear lighting for office, education, hospitality and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for indoor SELV installations
- Suitable for luminaires of protection class I

## Product family benefits

- Versatile QBM window driver up to 80 W and 750 mA
- Fully programmable via software (NFC)
- Very high efficiency
- High-quality dimming of 1...100 %
- Higher quality of light thanks to < 1% output ripple current
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

### Product family features

- Qualified Bluetooth mesh enabled by Silvair
- Supply voltage: 220...240 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Lifetime: up to 100,000 hType of protection: IP20
- SELV driver

Page 1 of 2

## Product family datasheet

## Application advice

For more detailed application information and graphics please see product datasheet.

## Sales and Technical Support

Sales and Technical Support www.osram.com

## Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.