# Lightbar FX1000-CB SM GEN 2



Single mount certified For individual installation



Up to 635 m long beam Improved far and near field illumination



Combo Beam Designed for both: far-field and near-field illumination



OSRAM

IP & IK protection classes Tested and validated in a DINcertified environmental simulation laboratory regarding extreme external influences such as water, dust, shocks, impacts, heat, cold, permanent vibrations and many more



#### Increased brightness for far and near field illumination

Particularly when driving on rural and dirt roads, a greater range of visibility can play a key role in ensuring safety. The LEDriving Lightbar FX1000-CB SM GEN 2 provides additional, near and far field illumination on dark roads with up to 8.000 Lumen. Even in poor visibility conditions or at dusk, the 40 high-performance LEDs reach a light distance of up to 635 meters and daytime lighting conditions with a color temperature of 6000 Kelvin. The driving light impresses with its special reflector design and ensure not only a modern and appealing look but also reduces glare for more visibility on the road. It can be used as both a supplementary LED high beam headlight and a powerful working light. The light is fully ECE-compliant in both versions and therefore suitable for use on roads. Additionally, OSRAM has developed a specially designed mounting kit, compatible with all driving lights of the Functional series FX Gen 2 for individual mounting. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. Complete polarity protection both prevents damage from excess voltage and contributes to a longer lifespan. The LEDriving Lightbar FX1000-CB SM GEN 2 has been tested and validated with the IP-Protection Classes IP6K8 &

IP6K9K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. Its variability gives the FX series a flexible range of uses. They can be attached to cars, trucks, agricultural machinery, commercial vehicles, construction vehicles, caravans, offroad vehicles and quads<sup>1)</sup>. OSRAM provides a 5-year guarantee<sup>2)</sup>.1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. 2) For precise conditions refer to: www.osram.com/am-guarantee

### Technical data

	Product information		tegory Global order ecific) reference LEDDL114-CB SM		Electrical Data				
Product description Application (Cate and Product spec					Nominal voltage			Nominal wattage	
Lightbar FX1000-CB SM GEN 2 LEDDL114-CB SM <sup>1)</sup>	Driving Light - Additional high beam application				12/24 V			140 W	
	Photome		tric Data	LED module information			Capabilities		
Product description	Test voltage	Nominal   flux	luminous	Number o LEDs per module	f Lifespan Tech Tc		Tech	nology	
Lightbar FX1000-CB SM GEN 2 LEDDL114-CB SM <sup>1)</sup>	13.2 V	8000 lm		40		> 5000 hr	LED	2)	
	Certificates	s & standard	is						
Product description	Approval marks –		Type of protection		Standards			ECE reference number	
Lightbar FX1000-CB SM GEN 2 LEDDL114-CB SM <sup>1)</sup>	E57 approv	val	IP6K8/IP6K9	К	ECE R	10, 2 x R11	2	50 + 50	
	Logistical o	lata		-	-	Information of EU Regu		(EC) 1907/2006	
Product description	Commodity code		Candidate list substance 1		CAS No. of substance 1		ance	Safe use instruction	
Lightbar FX1000-CB SM GEN 2 LEDDL114-CB SM <sup>1)</sup>	851220009	900	Lead		7439	9-92-1		The identification of the Candidate List substance is sufficient to allow safe use of the article.	

Product description	Declaration no. in SCIP database
Lightbar FX1000-CB SM GEN 2	c2b80793-fe0b-
LEDDL114-CB SM <sup>1)</sup>	4e19-b939-
	6a319f84b67b

<sup>1)</sup> Beam Pattern: Combo

 $^{2)}$  Light-emitting diode application

#### Download Data

	File
	User instruction LEDriving Lightbar FX1000-CB SM
-	User instruction GPRS_Safety symbols instructions
D	Movie application OSRAM LEDriving driving and working lights FX1000-CB SM (EN)
D	Movie application LEDriving D and W Image Video Bringing light to life (EN)
D	Movie application Working and Driving Lights Amarok Winter
D	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application LEDriving driving & working lights in application (EN)
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
D	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
D	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
D	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
D	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
Ľ	ref_pim_amsp_product360degreeimages LEDriving Lightbar FX1000-CB SM LEDDL114-CB SM

#### Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

#### Legal advice

1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.2) For precise conditions please refer to: www.osram.com/am-guarantee

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.